

PCB terminal block - ZFKDS 2,5-5,08-EX - 1732137

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PCB terminal block, Nominal current (Ex): 22 A, Nominal voltage (Ex): 137 V, Pitch: 5.08 mm, Number of positions: 1, Connection method: Spring-cage connection, Mounting: Soldering, Color: green

Product Features

- Desk shape with a clear delimitation of the conductor entry and the actuation opening (screwdriver shaft)
- Two solder pins for a high level of stability on the PCB
- Compact housing dimensions
- Modular design enables blocking for larger numbers of positions
- PCB single terminal block with spring-cage connection



Key commercial data

Packing unit	1 pc
Minimum order quantity	50 pc
Custom tariff number	85369010
Country of origin	Poland

Technical data

Dimensions

Pitch	5.08 mm
Pin dimensions	0,8 x 0,8
Hole diameter	1.3 mm

General

Range of articles	ZFKDS(A) 2,5-EX
Insulating material group	I
Nominal cross section	2.5 mm ²
Insulating material	PA
Solder pin surface	Sn

PCB terminal block - ZFKDS 2,5-5,08-EX - 1732137

Technical data

General

Inflammability class according to UL 94	V0
Number of positions	1

Classifications

eCl@ss

eCl@ss 4.0	27141111
eCl@ss 4.1	27141109
eCl@ss 5.0	27141190
eCl@ss 5.1	27141190
eCl@ss 6.0	27261101
eCl@ss 7.0	27440401
eCl@ss 8.0	27440401

ETIM


ETIM 3.0	EC001121
ETIM 4.0	EC002643
ETIM 5.0	EC002643

UNSPSC


UNSPSC 6.01	30211801
UNSPSC 7.0901	39121432
UNSPSC 11	39121432
UNSPSC 12.01	39121432
UNSPSC 13.2	39121432

Drawings

Drilling diagram



Dimensioned drawing



PCB terminal block - ZFKDS 2,5-5,08-EX - 1732137

Column photo




Abbildung kann gegebenenfalls weitere Produkte enthalten.

Phoenix Contact 2014 © - all rights reserved
<http://www.phoenixcontact.com>