


2-Port Metal DIN-Rail Mounting Module for Snap-In Keystone Jacks and Couplers, Silver, TAA

MODEL NUMBER: N063-002



Accepts snap-in keystone jacks and couplers to help you manage your DIN-rail network cable application.

Features

Organizes a Wide Variety of Ethernet Network Patch Cables in Your DIN-Rail Installation

This DIN-rail mounting module lets you manage network cable interconnectivity with two blank cutouts, which accommodate all snap-in keystone jacks and in-line couplers. Made from sheet metal with nickel plating, the N063-002 is quick and easy to install on a standard 35-millimeter DIN rail using the built-in mounting clip.

TAA-Compliant for GSA Schedule Purchases

The N063-002 is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

Specifications

| OVERVIEW | |
|--------------------------|--------------------------------|
| UPC Code | 037332276872 |
| Technology | Cat5/5e; Cat6; Cat6a |
| Firmware / Software Docs | |
| Offset Ports | No |
| PHYSICAL | |
| Primary Form Factor | DIN-Rail |
| Color | Silver |
| Material of Construction | SUS304 & SPCC NI PLATE (METAL) |

Highlights

- Heavy-duty metal construction ideal for industrial Ethernet network applications
- Dual blank cutouts compatible with all keystone jacks and couplers
- Built-in mounting clip attaches to standard 35 mm DIN rail with no tools needed
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Package Includes

N063-002 Metal DIN-Rail Mounting Module, 2 Ports

| | |
|--------------------------------------|--|
| Total Number of Ports | 2 |
| Shipping Dimensions (hwd / in.) | 2.10 x 4.50 x 8.00 |
| Shipping Weight (lbs.) | 0.12 |
| Unit Dimensions (hwd / in.) | 2.120 x 1.940 x 1.640 |
| ENVIRONMENTAL | |
| Operating Temperature Range | -13° to 122°F (-25° to 50°C) |
| Storage Temperature Range | -40° to 158°F (-40° to 70°C) |
| Operating Humidity Range | 10% to 85% RH, Non-Condensing |
| Storage Humidity Range | 10% to 85% RH, (Non-Condensing) |
| CONNECTIONS | |
| Number of Ports | 2 |
| Side A - Connector 1 | (2) KEYSTONE JACK CUTOUT |
| FEATURES & SPECIFICATIONS | |
| All-in-One Kit | No |
| Antibacterial | No |
| IP68 Rated | No |
| Numbered Ports | No |
| DIN Mountable | Yes |
| Keystone Jacks | Yes |
| Built-in Cables | No |
| Color-Coded Connections | No |
| EIA/TIA 2/32 Spacing | No |
| Labeled Ports | No |
| Down-Angled Ports | No |
| Panel Applications | Ethernet |
| STANDARDS & COMPLIANCE | |
| Product Compliance | CE (Europe); REACH; RoHS; UKCA; Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |



1000 Eaton Boulevard
Cleveland, OH 44122
United States



© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.