

# Eaton 48V Extended Battery Module (EBM) for 9SX1500 and 9SX1500G UPS Systems, Tower

#### MODEL NUMBER: 9SXEBM48









Provides extended runtime for compatible UPS systems in medical, light industrial, automation and other mission-critical IT applications where space is limited.

#### **Features**

#### Backup Battery Module Gives Your Compatible Eaton UPS System Extended Runtime

The 9SXEBM48 offers extended battery runtime when used in conjunction with Eaton's 9SX1500 and 9SX1500G 9SX UPS systems. It can also be daisy-chained for a maximum of four matching battery packs to deliver even longer extended-run operation. Heavy-gauge cabling with high-current DC connectors is included for safe, simple installation.

## **Highlights**

- Connects to select expandable Eaton 9SX UPS systems to add critical runtime
- Includes heavy-gauge battery cabling with high-current 48V DC connectors
- Daisy-chain connector supports additional battery packs for even longer runtime

## **System Requirements**

Compatible only with Eaton's 9SX1500 and 9SX1500G UPS systems

#### **Package Includes**

- 9SXEBM48 48V Extended Battery Module
- External battery cable
- · Quick Start Guide

# **Specifications**

OVERVIEW		
UPC Code	743172091055	
INPUT		
Input Phase	Single-Phase	
BATTERY		
DC System Voltage (VDC)	48	
PHYSICAL		
Rack Height	0U	
External Battery Pack Form Factor	Tower	
Installation Form Factors Supported with Included Accessories	Tower	



	·	
Unit Dimensions (hwd / in.)	9.900 x 6.300 x 15.100	
Unit Weight (lbs.)	52.900	
Unit Weight (kg)	24.00	
ENVIRONMENTAL		
Operating Temperature Range	32° to 104°F (0° to 40°C)	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS; REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (U.S. & Canada)	3-year limited warranty	
Warranty Details	Parts, electronics and batteries coverage, standard ground shipping, technical support	



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.