

www.lemo.com

# FLC.00.250.CTAC27

# SUMMARY

# Wires

Coax 1



Image is for illustrative purpose only

00 **Series** 

Male solder Termination type

IP rating 50

AWG wire size 0.00 - 0.00 Cable Ø 2.30 - 2.70 mm

**Status** active

Matching parts ERA.00.250.CTL

### **Download**

Request a quote

Catalog

# **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model FLC\*: Elbow (90°) plug with cable collet

Keying Circular, male

Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] **Housing Material** 

brass latch sleeve and mid pieces

Weight 3.88 g

### **Performance**

Configuration 00.250 : 1 Coax (50 Ohm)

Insulator T: PTFE **Rated Current** 4 Amps

# **Specifications**

Contact Type: Coaxial 50 Ohm (Solder)

Contact Dia.: 0.7 mm (0.028in) Bucket Dia.: 0.6 mm (0.024in) Test voltage: 2.1 kV (rms)

R (max): 6.1 mOhm

Vtest: 2100 V (AC), 3000 V (DC)

Impedance: 50 Ohm

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

VSWR: 1.09 + 0.11 \* f/GHz


# **Others**


Endurance (Shell): 5000 mating cycles

F ret (min): 100 N

Salt Spray Corrosion: >1000 hr

# **DRAWINGS**







## **Dimensions**

	A	Н	L	М
mm.	7.5	16.5	19.5	11.5
in.	0,30	0,65	0,77	0,45

# **RECOMMENDED BY LEMO**

## **Tools**

### **Cables**

17450	COPOLYMER	Black	
18700	PTFE	White	-= =-

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

18800	PTFE	White	
CCX.50.RG0.58AU14B	FEP	White	
CCX.50.RG1.74-U25N	PVC	Black	
CCX.50.RG1.74U25N	PVC	Black	
CCX.50.RG1.88AU24B	TFE	White	
CCX.50.RG1.88AU26B	PFA	White	
CCX.50.RG1.88AU26B	PTFE	White	
CCX.50.RG3.16BU26M	FEP	Brown	
CCX.75.RG1.79BU26M	FEP	Brown	
CCX.75.RG1.87AU26B	PFA	White	
CCX.75.RG1.87AU27B	PTFE	White	- = m -

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.