





THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMPHENOL CABLES ON DEMAND. ANY REPRODUCTION OR DISCLOSURE TO THIRD PARTIES, IN PART OR WHOLE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMPHENOL CABLES ON DEMAND IS PROHIBITED.

REV.	DESCRIPTION	DATE	APPROVED
A0	NEW RELEASE	23/Jun/2021	
A1	Added Ue Information, LABEL 2 BAG.	26/Aug/2021	
A2	Updated Label Distance.	26/Aug/2021	
A3	Add LENGTH & PIN Color Table Page	10/Sep/2021	
A4	Added the length for the color black & blue.	15/Sep/2021	



CABLE MARKING:
 Amphenol Cables on Demand TYPE CM 28AWG 4PR 75°C
 (UL) e(UL) E814104 T1M/E1A-588-C-2 UTP CAT 6

PIN OUT: T568B	COLOR
PLUG 1	PLUG 2
PIN1	PIN1
PIN2	PIN2
PIN3	PIN3
PIN4	PIN4
PIN5	PIN5
PIN6	PIN6
PIN7	PIN7
PIN8	PIN8



- NOTE:
- 1.WORKING TEMPERATURE RANGE:-25°C TO 75°C
 - 2.CONTACT RESISTANCE:<=30 mΩ
 - 3.INSULATION RESISTANCE:>=100 MΩ/300V
 - 4.TENSILE STRENGTH(CABLE TO PLUG): 7.7kgf
 - 5.INSERTING/MATING:1000 TIMES CYCLES MIN

Cable & SR Color:Black,Blue, Yellow, Green, Red, White



UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:		EAR NO.		Amphenol Cables on Demand 20 VALLEY ST. ENDICOTT, NY 13760	
DECIMALS	±.X	APPROVALS	DATE	DRAWN	23/Jun/2021
X	±.XX	LF		CHECKED	23/Jun/2021
XX	±.XXX	BA		RESP ENG	
XXX	±.XXX			MFG ENG	
THIRD ANGLE PROJECTION		SIZE	DWG. NO.	REV.	
		A	MP-64RJ4528GX-XXX	A4	

NOTES: UNLESS OTHERWISE SPECIFIED