"X" DIM ASS'Y P/N CA6A808P03990 3 FT. 3 1/2 IN. ±2 IN. [1M ±50.8mm] NOTES: CA6A808P07990 6 FT. 7 IN. ±2 IN. [2M ±50.8mm] FINISHED PRODUCT TO BE COILED
OVERMOLD BOOT MATERIAL: PVC, BLACK
ELECTRICAL TEST: 100% CONTINUITY CA6A808P19790 16 FT. 5 IN. ±4 IN. [5M ±101.6mm] CA6A808P39490 32 FT. 9 3/4 IN. ±8 IN. [10M ±203.2mm] 4. ALL DIMENSIONS ARE REFERENCE EXCEPT THOSE WITH A TOLERANCE CA6A808PXXX90 -CABLE LENGTH IN "INCHES" CUSTOMER PRINT – "X" DIM O-RING 2,470 MAT'L: SILICONE, RED 62.7 KEY cenzall' BLUNT CUT (2) 16 AWG CONDUCTORS (6) 26 AWG CONDUCTORS JACKET: PRESSURED PVC, BLACK END "A" **FACE VIEW** COUPLING RING Ø .270 O.D. NOM. MAT'L: UV PBT, BLACK 300 VOLTS STRAIGHT OVERMOLDED CABLE CONNECTOR, MALE MAT'L: UV PBT, BLACK (2) #16 PIN CONTACTS (6) #26 PIN CONTACTS MAT'L: GOLD PLATED COPPER ALLOY CA6A808PXXX90 **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CORPORATION. ANY REPRODUCTION, MA 07-13-21 DRAWING CREATED PER DOR 21-109361DS DISCLOSURE, OR USE OF THIS REV. INIT. DATE DESCRIPTION DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN WRITING BY CONXALL CORPORATION. 07-13-21 MA WIRE COLOR CODE SOINLIG 601 E. WILDWOOD VILLA PARK, IL 60181 POS. 1 POS. 2 POS. 3 POS. 4 POS. 5 POS. 6 POS. 7 POS .8 APPROVED BY: CABLE ASSEMBLY BRN RED YEL GRY BLK WHT GRN BLU DATE: 2#16/6#26 PIN CONTACTS MINI-CON-X MIXED SIGNAL FLEX OM STANDARD PRODUCT DIMENSIONS IN BRACKETS [] ARE IN SCALE NTS SHEET 1 OF 1 26 AWG 26 AWG 26 AWG 26 AWG 26 AWG 26 AWG 16 AWG 16 AWG MILLIMETERS UNLESS INDICATED **Rohs Compliant** PART NUMBER: CA6A808PXXX90 CA6A808PXXX90