



NOTES:

1. METALSHELLS: STEEL; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0; GREEN
3. SIGNAL CONTACTS: COPPER ALLOY
PLATING: GOLD FLASH over NICKEL
4. NO CONTACTS ON POS. A1 + A2
5. THREADED REAR SPACERS: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
6. SLEEVES: COPPER ALLOY; min. 200µin TIN over 80µin NICKEL
7. P.C.B. HOLE DRILLINGS ON SHEET 2
8. MAXIMUM TORQUE VALUE FOR THREAD: 6 in.LB
9. CONNECTOR IS PART MARKED: **3043W2PAR99A50X CONEC ABC**

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm	scale: 2:1 (5:1)		
				material: SEE NOTES		
	drawn	30.06.14	Henneboel		D-SUB COMBINATION MALE 43W2P with threaded rear spacer	
	appd.	01.07.14	Lehmenkühler			
	norm					
	d-old					
	rev. a	Original			dwg no:	DIN-A3
	rev.	description			date	name
					part no:	3043W2PAR99A50X

