



- CONNECTOR MATE WITH ANY 5 POSITION PLUG IN AMP LINE 50™ SERIES.
- HOUSING: POLYESTER, FLAME RETARDANT 94V-0 RATING TO MEET ASTM D 388, 3-CELL STEEL REIN. ASTM A 105. CONTACTS: PHOSPHOR BRONZE PER QQ-B-750. EX. PLATED: BRASS. SCREW LOCK: ZINC. INSERTS: ZINC. BUSHINGS: COPPER ALLOY.
- 5 P.L.C. .000200 MIN. TIN OR TIN LEAD. CONTACTS: SEE TABLE. BUSHINGS: TYN. SCREW LOCK: GILAS 2 ROPAD. BOARD LOCK: TYN. PAD. INSERTS: CLEAR COPOLYATE.
- 60# BUSHINGS PER QQ-B-60000, 60# BUSHING PER QQ-B-290, TIN PLATING PER MIL-STD-10727.
- 60# FLASH FOR A DIE FACE OF .100 MIN FROM MATING END. .000200-.000200 IN. DIA. OR BR. 60# 1.4-1.4. IN. REPLICATION END, ALL OVER .000200 IN. DIA. ON THE 1ST CONTACT.
- .000200 GOLD FOR A DIE FACE OF .100 MIN FROM MATING END. .000200-.000200 IN. DIA. OR BR. 60# 1.4-1.4. IN. REPLICATION END, ALL OVER .000200 IN. DIA. ON THE 1ST CONTACT.
- SCREWS & WASHERS REQUIRED FOR EACH CONNECTOR ASSEMBLY SHALL BE BLUE PASSED 201-100-0111 CONN. DIV. OR 201-100-0111.
- DIMENSION APPLIES TO CENTER LINE OF CONTACTS.

DESCRIPTION	ITEM #	QUANTITY	UNIT	PART NUMBER
HEAD - 1/4 IN DIA	727812-8			727812-8
HEAD - 1/4 IN DIA	727812-9			727812-9
HEAD - 1/4 IN DIA	727812-6			727812-6
HEAD - 1/4 IN DIA	727812-5			727812-5
HEAD - 1/4 IN DIA	727812-4			727812-4
HEAD - 1/4 IN DIA	727812-3			727812-3
HEAD - 1/4 IN DIA	727812-2			727812-2
HEAD - 1/4 IN DIA	727812-1			727812-1
BUSHING HARDWARE				
CONTACT PIN				
PART NUMBER				