

| ILTS SERIES

SUBMERSIBLE DUAL LEVEL & TEMPERATURE TRANSMITTER



The ILTS is designed for use in continuous submersion in liquids such as water, oil and fuels. The probe uses the latest piezo-resistive media-isolated silicon sensing technology and a stainless steel diaphragm. Housed within a 316L stainless steel, or high grade Duplex stainless steel housing, this submersible transmitter is the ideal product for hydrostatic level measurement where temperature is also a critical part of the measurement.

It offers excellent stability, repeatability and resolution, as required for use in rivers and reservoirs.

This type incorporates a Class 'B' accuracy platinum resistance thermometer.

Every device is temperature compensated, calibrated and supplied with a traceable serial number and calibration data.*

*Calibration data is supplied as a sticker affixed to the product packaging - do not discard.

Custom versions can be made for particular applications.

Features

- Stainless steel, piezo-resistive sensor
- Level accuracy: <0.1% FS BFSL
- Pressure ranges from 5mWG to 10mWG
- Temperature range: -20 to +60°C
- Dual independent 4-20mA outputs

Suitable Applications

- River level & temperature
- Tank level & temperature
- Aquifer level & temperature
- V-notch weir flow measurement
- Reservoir level & temperature
- Borehole level & temperature
- Environmental monitoring

SPECIFICATIONS

Temperature Range

Temperature Range	°C	-20 to +60
--------------------------	----	------------

Level Performance

Accuracy (Non-linearity & Hysteresis)	<±0.1% / FS (BFSL)	
Setting Errors (Offsets)	Zero & Full Scale, <±0.5% / FS	
Permissible Load	$R_{max} = [(Voltage\ Supply - 9) / 0.02] Ohms$	
Influence Effects	Supply	<0.005% FS / 1V
	Load	0.05% FSO / kOhm

Temperature Performance

Measurement Accuracy	(mA output/2000) or 5µA (whichever is the greater)
Thermal Drift	1 µA/°C
Loop Voltage Effect	0.2µA/V
Maximum Output Load	$[(V_{supply} - 10) / 21]$ kOhms (Example: 700 Ohms @ 24V)
Output Timing	Transmitter start up time: 4 seconds (I out <4mA during start up)
	Warm up time: 1 minute to full accuracy
	Update time: 500ms
	Response time: 1 second

Output Signal & Supply Voltage

	Output	Supply Voltage	Connection	Wire Colors
Level (2-wire)	4 - 20mA	9 – 32V dc	+ve Supply	Red
			-ve Supply	Blue
			Ground & Cable Screen	Green
Temperature (2-wire)	4 - 20mA	9 – 32V dc	+ve Supply	White
			-ve Supply	Yellow
			Ground & Cable Screen	Green

Electrical Protection

Supply Reverse Polarity	No damage/no function
Lightning Protection	Internally fitted
Electromagnetic Compatibility	CE EMC directive · EN 61326-1:2013

Mechanical Stability

Shock	100g / 11ms
Vibration	10g RMS (20 - 2000 Hz)

Temperature & Thermal Effects

Media Temperature	-20°C (Non-freezing) to +60°C
Storage Temperature	-20°C to +70°C
Compensated Temperature Range (Level only)	+5°C to +75°C
Thermal Zero Shift (TZS) (Level only)	<±0.02% /FS/°C
Thermal Span Shift (TSS) (Level only)	<-0.015% /°C
Thermal Drift (Temperature only)	1µA/°C

Material

Housing	316L Stainless Steel
"O" Ring Seals	Viton
Diaphragm	316L Stainless Steel
Cable Sheath Material	PUR
Media Wetted Parts	Housing, "O" ring seal, diaphragm, cable sheath

Miscellaneous

Current Consumption	Level transmitter limits at 28mA
	Temperature transmitter limits at 21.5mA
Weight	Transmitter: approx 300g inc. nose cone
	Cable: 48g per meter
Installation Position	Any, small zero shift when tilted through 90°
Operational Life	> 100x 10 ⁶ cycles



PRESSURE RANGES


Nominal Pressure, Gauge	mWG	5	10
Permissible Overpressure	mWG	50	50

Part No	Pressure Range	Cable Length
ILTS-G0500-007	0-5mWG (0-197"WG)	7M
ILTS-G1000-015	0-10mWG (0-394"WG)	15M



DIMENSIONS

All dimensions are in millimeters.



Installation Note.
The vented cable is fitted with a filter (shown below) to prevent the entry of moisture. If removed, ensure vent tube is positioned in a clean, dry area.



Sensata Technologies, Inc. ("Sensata") data sheets are solely intended to assist designers ("Buyers") who are developing systems that incorporate Sensata products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products. Sensata data sheets have been created using standard laboratory conditions and engineering practices. Sensata has not conducted any testing other than that specifically described in the published documentation for a particular data sheet. Sensata may make corrections, enhancements, improvements and other changes to its data sheets or components without notice.

Buyers are authorized to use Sensata data sheets with the Sensata component(s) identified in each particular data sheet. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER SENSATA INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN. SENSATA DATA SHEETS ARE PROVIDED "AS IS". SENSATA MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE DATA SHEETS OR USE OF THE DATA SHEETS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. SENSATA DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO SENSATA DATA SHEETS OR USE THEREOF.

All products are sold subject to Sensata's terms and conditions of sale supplied at www.sensata.com SENSATA ASSUMES NO LIABILITY FOR APPLICATIONS ASSISTANCE OR THE DESIGN OF BUYERS' PRODUCTS. BUYER ACKNOWLEDGES AND AGREES THAT IT IS SOLELY RESPONSIBLE FOR COMPLIANCE WITH ALL LEGAL, REGULATORY AND SAFETY-RELATED REQUIREMENTS CONCERNING ITS PRODUCTS, AND ANY USE OF SENSATA COMPONENTS IN ITS APPLICATIONS, NOTWITHSTANDING ANY APPLICATIONS-RELATED INFORMATION OR SUPPORT THAT MAY BE PROVIDED BY SENSATA.

Mailing Address: Sensata Technologies, Inc., 529 Pleasant Street, Attleboro, MA 02703, USA.

CONTACT US

+44 (0)1202 897969
c3w_sales@sensata.com
Cynergy3 Components Ltd.
7 Cobham Road,
Ferndown Industrial Estate,
Wimborne, Dorset,
BH21 7PE, United Kingdom