



RECOMMENDED STRIP LENGTH

OBSOLETE	AT&T 735A	1.07	0.42	4.52	1.78	58425-2	5	TUBING PLASTIC	4	TUBING METAL	3	FERRULE	2	CONTACT	1	PLUG ASSY	PART NUMBER
OBSOLETE	RG-59 TYPE WITH .031 DIA CENTER CONDUCTOR-BELDEN 9240,9259 & 9266	1.07	0.42	6.48	2.55	58425-1	-	-	-	-	9-413658-2	1-413746-0	413947-2	1-5413588-0			
OBSOLETE	RG-179/U/1.79A/U/1.79B/U/1.87/U & 187A/U	1.07	0.42	4.52	1.78	58425-2	227194-2	1-222001-0	1-222001-0	9-413658-0	1-413746-0	413947-1	413947-1	5413588-9			
OBSOLETE	AT&T KS 19224 12	1.07	0.42	4.52	1.78	58425-2	227194-2	1-222001-0	1-222001-0	9-413658-2	1-413746-5	413947-2	413947-2	5413588-8			
OBSOLETE	RG-59/U/59A/U & 59B/U	1.07	0.42	6.48	2.55	58425-1	-	-	-	9-221132-1	413746-5	413947-1	413947-1	5413588-2			

FOR USE WITH CABLE

THIS DRAWING IS A CONTROLLED DOCUMENT

DESCRIPTION	REVISION	DATE	BY	CHKD	APP'D
PLUG, RIGHT ANGLE, HEX CRIMP, 75 OHM/BNC	1	00779	5413588		