1094595

https://www.phoenixcontact.com/us/products/1094595

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Prewired control cabinet with power supply, surge protective device, and circuit breaker for use with remote control and monitoring devices



Product description

To simplify the selection and installation of wireless devices, Phoenix Contact offers the RTU READY... enclosure system to house radios, PLCs, or other control products. The prewired control cabinet provides a 24 V DC power supply and surge protection for line power and antenna connections, and terminal blocks for easy connectivity, all mounted on standard NS 35 mounting rail.

The selected components provide a robust housing with reliable power. Simply add a radio, antenna, or controller to complete the system.

Your advantages

- · 100 V AC ... 240 V AC nominal input voltage range
- 24 V DC supply voltage
- · Prewired cabinetry with extra terminal blocks for simple, flexible installation
- UL 508A Listed
- · COAXTRAB surge protection for antenna connection

Commercial data

Item number	1094595
Packing unit	1 pc
Sales key	DT02
Product key	DTHDCA
GTIN	4063151030711
Weight per piece (including packing)	0.01 g
Weight per piece (excluding packing)	0.01 g
Country of origin	US

HŒR

1094595

https://www.phoenixcontact.com/us/products/1094595



Set consists of

UNO-PS/1AC/24DC/90W/C2LPS - Power supply unit

2902994

https://www.phoenixcontact.com/us/products/2902994



Primary-switched UNO POWER power supply for DIN rail mounting, input: 1-phase, output: 24 V DC/90 W

RTU READY UPS 161408 - Control cabinet

1094596

https://www.phoenixcontact.com/us/products/1094596



Prewired control cabinet with power supply, battery backup, surge protective device, and circuit breaker for use with remote control and monitoring devices

1094595

https://www.phoenixcontact.com/us/products/1094595



Technical data

Notes

Trade restriction	
CE note	The products are offered exclusively for export outside the EU and the European Economic Area.
Product properties	
Product type	Control box
electrical properties	
Supply	
Supply voltage range	85 V AC 264 V AC
Typical current consumption	3.75 A
Dimensions	
Width	434 mm
Height	492 mm
Depth	271 mm
laterial specifications	
Housing material	Polycarbonate
nvironmental and real-life conditions	
Ambient conditions	
Ambient temperature (operation)	-25 °C 70 °C
tandards and regulations	
Standards	
Standards/regulations	UL 508A

1094595

https://www.phoenixcontact.com/us/products/1094595



Classifications

ECLASS

ECLASS-13.0	27370190
ECLASS-11.0	27142422

ETIM

ETIM 7.0	EC000268

1094595

https://www.phoenixcontact.com/us/products/1094595



Environmental product compliance

REACh SVHC	Lead 7439-92-1
	Cadmium oxide 1306-19-0

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com