

RS 32 24VDC LD LP 2U

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image

Similar to Illustration

General ordering data

Version	RS-SERIES, Relay module, Number of contacts: 2, CO contact AgNi 90/10, Rated control voltage: 24 V DC $\pm 10\%$, Continuous current: 4 A, Screw connection
Order No.	8607480000
Type	RS 32 24VDC LD LP 2U
GTIN (EAN)	4032248266982
Qty.	10 pc(s).
Delivery status	This article will no longer be available in the future.
Available until	2022-11-25

RS 32 24VDC LD LP 2U

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 50.3 g

Temperatures

Storage temperature	-40 °C...60 °C	Operating temperature	-25 °C...40 °C
Operating temperature, min.	-25 °C	Operating temperature, max.	40 °C

Control side

Rated control voltage	24 V DC \pm 10 %	Status indicator	red LED
Protective circuit	Free-wheeling diode, Reverse polarity protection		

Load side

Rated switching voltage	250 V AC	Continuous current	4 A
AC switching capacity (resistive), max.	1000 VA	Switch-off delay	\leq 10 ms
Contact type	2 CO contact (AgNi 90/10)		

General data

Colour orange

Insulation coordination

Rated voltage	300	Dielectric strength to mounting rail	4 kV _{eff} / 1 Min.
Impulse withstand voltage	4 kV (1.2/50 μ s)	Protection degree	IP20

Connection data

Wire connection method Screw connection

Classifications

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ETIM 8.0	EC001437	ECLASS 9.0	27-37-16-01
ECLASS 9.1	27-37-16-01	ECLASS 10.0	27-37-16-01
ECLASS 11.0	27-37-16-01	ECLASS 12.0	27-37-16-01

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	7b5ffb72-271d-4c73-8b09-bd0aaee3697a

Approvals

Approvals



ROHS Conform

RS 32 24VDC LD LP 2U

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Downloads

Catalogues

[Catalogues in PDF-format](#)