

4

3

2

1

© 2019 TE Connectivity. All Rights Reserved.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
A7		REVISED PER ECR-22-112591	23NOV22	DT	EW

DETAIL A
SCALE 3:1

SEE DETAIL A

SCALE 2:1

SCALE 3:1
PCB LAYOUT

NOTE:

- ACCUMULATING TOLERANCE : $\pm 1.5\text{mm}/20$ PITCH.
- TAPE MUST NOT PROTRUDE FROM BACKING PAPER.
- APPLICABLE P.C.B HOLE DIA: $1.0(+0.1/-0)\times 6.0(+/-0.1)$.
- APPLICABLE PC BOARD THICKNESS: $t=1.6\text{mm}$.
- APPLICATION: APPLICABLE TO .250 FASTON RECEPTABLE.
- THE CORNER: NOT INSTRUCTED R or C SHOULD BE 0.2.
- 2358709-2 IS FOR POD-LOK, DIM $4.1+/-0.1$
- WITHOUT DIMPLE FOR TCL

8	7	TIN	BRASS	.250 TAPING TAB NODIMPLE	2358709-3
	7	TIN	BRASS	.250 TAPING TAB	2358709-2
		TIN	BRASS	.250 TAPING TAB STANDARD	2358709-1
		PLATING	RAW MATERIAL	DESCRIPTION	PN

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DON TANG 21JUN2019			
DIMENSIONS: mm		CHK DAISY LI			
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD TIM DING 21JUN2019	NAME TAPING TAB .250 SERISE		
		PRODUCT SPEC 108-106425	RESTRICTED TO		
0 PLC \pm 1 PLC ± 0.2 2 PLC \pm 3 PLC \pm 4 PLC \pm ANGLES $\pm 2^\circ$		APPLICATION SPEC 114-2115	SIZE A3	CAGE CODE 00779	DRAWING NO C-2358709
MATERIAL -		FINISH -	WEIGHT -	SCALE 1:1	
		CUSTOMER DRAWING		SHEET 1	OF 1
				REV A7	

printed on 23 Nov 2022 22:14 (China Standard Time) from ES23083

A

D

C

B

1470-19 (3/13)