Dialight

557 Series High Intensity LED Panel Mount Indicators for ¹¹/_{16"} Mounting Hole Watertight



FEATURES / BENEFITS

- Daylight viewability
- ▲ Tamperproof /Designed for high durability
- ▲ Long life, up to 100k hours
- Uniform illumination
- ▲ Low profile flat lens design

APPLICATIONS


The 557 Series LED Panel Mount Indicators incorporate both InGaN and AlInGaP technologies to offer higher intensities. This is a highly durable package, designed to withstand outdoor applications susceptible to rain, dust, and sunlight.

- Instrument panels
- Vending, gaming
- Transportation rail, bus, airline
- ... and many more!

Lane control

SPECIFICATIONS

- Available in red, yellow, green, blue, and white
- ▲ Voltage range of 5, 12, 24 VDC
- A Housing material: White polycarbonate
- Lens material: Polycarbonate 94 VO
- Watertight seal from front of panel meets MIL-L-3661B Maximum mounting torque - 15 in./lb.
- ▲ Front mounting in ¹¹/_{16"} clearance hole
- Operating temperature: -25°C to +85°C
- ▲ Storage temperature: -30°C to +100°C



Dialight reserves the right to make changes at any time in order to supply the best product possible.

Please see back of page for part numbers and additional specifications.



Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com

a Roxboro Group Company

MDEL557U001_B

Dialight

557 Series High Intensity LED Panel Mount Indicators for ¹¹/_{16"} Mounting Hole **Watertight**

PART NUMBER	COLOR	VOLTAGE (VDC)	CURRENT (mA)	TYPICAL INTENSITY (fL)
557-1502-203	Red	5	80	1000
557-1602-203	Green	5	16	1000
557-1702-203	Yellow	5	80	1000
557-1802-203	Blue	5	16	250
557-1002-203	White	5	16	700
557-1503-203	Red	12	20	1000
557-1603-203	Green	12	16	1000
557-1703-203	Yellow	12	20	1000
557-1803-203	Blue	12	16	250
557-1003-203	White	12	16	700
557-1505-203	Red	24	20	1000
557-1605-203	Green	24	16	1000
557-1705-203	Yellow	24	20	1000
557-1805-203	Blue	24	16	250
557-1005-203	White	24	16	700

LED Panel Mount Indicator Selection

Dialight's line of LED Panel Mount Indicators are available in a variety of sizes and options. Please visit our website for more information.

www.dialight.com

- ▶ .156" 558 Series
- ▶ .250" 559 Series
- ▶ 5mm *605 Series*
- ▶ 6mm 606 Series
- ▶ 7mm 607 Series

- ▶ 8mm 608 Series
- ▶ 9mm *609 Series*
- ▶ 10mm 610 Series
- ▶ 11/16" Watertight 557 Series
- ▶ 1" Watertight *556 Series*

Custom capabilities: Please contact factory regarding customizing these indicators to your specific requirement.

Dialight reserves the right to make changes at any time in order to supply the best product possible.



Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com

a Roxboro Group Company

MDEL557U001_B