



SPECIFICATION CONTROL DRAWING

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES, LTD. ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED. ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.

REV	DESCRIPTION	DWN	DATE	APPROVED
A	ENGINEERING RELEASE	WMD	6/13/95	R. RICE
B	ADD ELEC SPECS	KMM	9/5/96	R. RICE



RECOMMENDED MOUNTING HOLE
 .126 [3.20] MAX PANEL THICKNESS

SPECIFICATIONS:

IMPEDANCE: 50 OHMS
 WORKING VOLTAGE: 335 VRMS @ SEA LEVEL
 FREQUENCY RANGE: 0-12.4 GHz

ITEM	DESCRIPTION	QTY	MATERIAL	FINISH
6	LOCK WASHER [LKW-250]	1	BRASS	NICKEL
5	HEX NUT [HEX-250-365]	1	BRASS	NICKEL
4	DIELECTRIC	1	PTFE	NONE
3	DIELECTRIC	1	PTFE	NONE
2	PIN	1	BeCu	GOLD
1	BODY	1	BRASS	NICKEL

DIMENSIONS ARE IN INCHES AND [MILLIMETERS]
 UNLESS OTHERWISE NOTED TOLERANCES ARE:
 DECIMALS DIAMETER

DRAWN
 K. MAXWELL
 9/5/96

CHECKED
 ORU DRAWN
 K. MAXWELL
 6/13/95

RF connectors
 DIVISION OF RF INDUSTRIES, LTD.
 7610 MIRAMAR RD
 SAN DIEGO, CA 92126
 (619)549-6340
 (619)549-6345 FAX

RSA-3250

SMA FEMALE BULKHEAD, SOLDER, FRONT MOUNT

SIZE	CABLE GROUP	DWG NO.	REV
A	N/A	8519	B
SCALE:	CAD FILE	SHEET	OF
2:1	13ARC B	1	1

008974