



Metric

4 Type

A Without bores

Metric table

Dimensions in: millimeters - inches

| 2 | | | 3 | | | |
|-------------|-------------|-------------|-------------|------------|------------|------------|
| l_1 | | | l_2 | d | h | s |
| 60 2.36 | 120 4.72 | 160 6.30 | 30 1.18 | 6 0.24 | 12 0.47 | 5 0.20 |
| 60 2.36 | 120 4.72 | 160 6.30 | 40 1.57 | 6 0.24 | 12 0.47 | 5 0.20 |
| 60 2.36 | 120 4.72 | 160 6.30 | 50 1.97 | 6 0.24 | 12 0.47 | 5 0.20 |
| 60 2.36 | 120 4.72 | - | 60 2.36 | 6 0.24 | 12 0.47 | 5 0.20 |
| 160 6.30 | - | - | 60 2.36 | 8 0.31 | 15 0.59 | 6 0.24 |
| 160 6.30 | 200 7.87 | - | 80 3.15 | 8 0.31 | 15 0.59 | 6 0.24 |
| 160 6.30 | 200 7.87 | - | 100 3.94 | 8 0.31 | 16 0.63 | 7 0.28 |
| 220 8.66 | - | - | 100 3.94 | 13 0.51 | 26 1.02 | 10 0.39 |

Specification

- Body
Steel profile
Rolled, scaled or drawn
Plain finish

1

5

ST

BL

- Pin
Steel
- Load Rating Information → page 2088
- RoHS compliant

On request

- With loose pin
- With brass pin
- With lubricating nipple
- With bore holes
- Other dimensions
- Other finishes

Information

GN 1366 hinges are made of rolled or drawn steel profiles and are very robust.

Type A can be assembled by welding or done via custom made holes in the hinge.

Thanks to the standard dimensions, special applications and specific solutions can be realized even in relatively small quantities.

see also...

- List of Hinge Types → page 1324
- Lift-Off Hinges GN 128 (Steel, Weldable) → page 1414
- Lift-Off Hinges GN 128.2 (Stainless Steel, Weldable) → page 1415
- Sheet Metal Hinges GN 136 (Steel or Stainless Steel) → page 1338 / 1339
- Sheet Metal Hinges GN 1362 (Stainless Steel, Weldable) → page 1340

How to order

GN 1366-ST-60-50-A-BL

- 1 Material
- 2 Width l_1
- 3 Length l_2
- 4 Type
- 5 Finish