



All 3M Products Innovation About 3M

Search

United States [Change](#)

Oil & Gas

[Industry Solutions](#) | [Products](#) | [Resources](#) | [About 3M Oil & Gas](#)

[Contact Us](#)

[United States](#) > [All 3M Products](#) > [Safety and Security](#) > [Oil & Gas](#) > [Products](#)

[Oil & Gas](#) > [Industrial Adhesives & Tapes](#) > [Fasteners](#) > [3M™ Hook and Loop](#) > 3M™ Fastener SJ3526N Hook White, 1 in x 50 yd 0.15 in (3.8 mm) Engaged Thickness, 3 per case Bulk

## 3M™ Fastener SJ3526N Hook White, 1 in x 50 yd 0.15 in (3.8 mm) Engaged Thickness, 3 per case Bulk

3M ID 70070970036 UPC# 00021200862441 3M Product Number 86244 3M Product Number SJ3526N




3M™ Fastener SJ3526N is a high performance PSA nylon hook with a rubber adhesive and white polypropylene film liner.

- White colored hook fastener backed with a high performance, rubber based adhesive designed for indoor applications requiring medium temperature resistance.
- Woven nylon is durable for thousands of closures.
- Aerospace, Electronics, Construction, Specialty Vehicle, Military, Medical, Furniture, General Industrial
- Securing Fabric to Furniture Cushions, Airplane Seating, Carpet Panel Attachments, Uniforms, Gloves and Clothing

[Buy at Shop3M.com](#)

**Need Help?**

**Questions?** We can help [Contact Us](#)



Like [Sign Up](#) to see what your friends like.

[Overview](#) | [Support](#)

This product is coated with a high performance rubber adhesive. Medium temperature performance. Bonds well to paper and cardboard, paint, bare and painted metal, glass, sealed wood and many plastics. Designed for indoor use.

**Specifications**

<b>Adhesive Type</b>	High Performance Rubber Adhesive
<b>Brand</b>	3M
<b>Closure Life</b>	5000
<b>Color</b>	White
<b>Engaged Thickness</b>	0.15 Inch
<b>Flame Retardant</b>	No
<b>Hook/Loop</b>	Hook
<b>Industry - Use</b>	Construction, Electronics, Furniture, General Industrial, Medical, Military & Government, MRO, Specialty Vehicle, Transportation
<b>Length</b>	50 Linear Yard
<b>Length (metric)</b>	45.72 Linear Metre

<b>Liner Thickness</b>	3 Milli-inch (mil)
<b>Liner Type</b>	White Polyethylene with Red Logo
<b>Low Profile</b>	No
<b>Material</b>	Nylon
<b>Maximum Operating Temperature (Celsius)</b>	49 Degree Celsius
<b>Maximum Operating Temperature (Fahrenheit)</b>	120 Degree Fahrenheit
<b>Product Form</b>	Roll
<b>Units per Case</b>	3
<b>Width</b>	1 Inch
<b>Width (metric)</b>	25.40 Millimetre

**3M:** [News](#) | [Careers](#) | [Partners & Suppliers](#) | [Investor Relations](#) | [MSDS Search](#) | [Transport Information Search](#) | [Contact 3M](#)

[Legal Information](#) | [Privacy Policy](#)

© 3M 2014. All Rights Reserved.

