



wire connector CU 2 cables with control wire voltage tap-off 3 units  
accessory for: 3VA5/6 400/600

Model	
product brand name	SETRON
product designation	accessories
Product version	circular conductor terminal
Accessories	Wire connector
General technical data	
designation / of the terminal	TC2.4
Connections according IEC	
stripped length	31 / 58,5 mm
Connections according UL	
permissible temperature / of connectable conductor / according to UL 486A-486B	90 °C
stripped length	1.2 / 2.3 in
connectable conductor cross-section	
• for copper cable / stranded / minimum	2/0 AWG
• for copper cable / stranded / maximum	600 kcmil
• for copper cable / finely stranded / minimum	2/0 AWG
• for copper cable / finely stranded / maximum	600 kcmil
tightening torque / when using copper cables	
• stranded	2/0 - 600 kcmil: 375 lb-in
• finely stranded	2/0 - 600 kcmil: 375 lb-in

Further information	
<b>Information- and Downloadcenter (Catalogs, Brochures,...)</b>	
<a href="http://www.siemens.com/lowvoltage/catalogs">http://www.siemens.com/lowvoltage/catalogs</a>	
<b>Industry Mall (Online ordering system)</b>	
<a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9473-0JL23">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9473-0JL23</a>	
<b>Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)</b>	
<a href="https://support.industry.siemens.com/cs/ww/en/ps/3VA9473-0JL23">https://support.industry.siemens.com/cs/ww/en/ps/3VA9473-0JL23</a>	
<b>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)</b>	
<a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9473-0JL23">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9473-0JL23</a>	
<b>CAX-Online-Generator</b>	
<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>	
<b>Tender specifications</b>	
<a href="http://www.siemens.com/specifications">http://www.siemens.com/specifications</a>	

last modified:

12/20/2020 

