



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors >

Crimp-on-Snap-in Housing



Connector System: **Wire-to-Board**

Number of Positions: **10**

Centerline (Pitch): **1.27 mm [.05 in]**

Row-to-Row Spacing: **2 mm [.059 in]**

Number of Rows: **2**

[All Crimp-on-Snap-in Housing \(9\)](#)

Features

Product Type Features

| | |
|------------------------------------|---------------|
| Ribbon Cable Connector Header Type | Shrouded |
| Connector Product Type | Housing |
| Connector System | Wire-to-Board |
| Connector & Housing Type | Plug |
| Connector & Contact Terminates To | Wire & Cable |

Configuration Features

| | |
|---------------------|----|
| Number of Positions | 10 |
| Number of Rows | 2 |

Electrical Characteristics

| | |
|-----------------------|---------|
| Insulation Resistance | 1000 MΩ |
| Operating Voltage | 100 VAC |

Body Features

| | |
|-----------------------|----------|
| Daisy Chain | Without |
| Primary Product Color | Red |
| Connector Profile | Standard |

Contact Features

| | |
|--|--|
| | |
|--|--|



| | |
|--|-----------------|
| Contact Type | Socket |
| Contact Mating Area Plating Material | Tin |
| PCB Contact Termination Area Plating Material Finish | Matte |
| Contact Underplating Material | Nickel |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Base Material | Phosphor Bronze |
| Contact Current Rating (Max) | 1.5 A |

Termination Features

| | |
|------------------------------------|--------------|
| Termination Method to Wire & Cable | Crimp & Snap |
|------------------------------------|--------------|

Mechanical Attachment

| | |
|---------------------------------------|------------------|
| Mating Alignment | With |
| Contact Retention Type Within Housing | Snap-In |
| PCB Mount Alignment | Without |
| Mating Alignment Type | Polarization |
| Mating Retention | With |
| Mating Retention Type | Contact Friction |

Housing Features

| | |
|--------------------|------------------|
| Housing Material | PBT GF |
| Centerline (Pitch) | 1.27 mm [.05 in] |

Dimensions

| | |
|-----------------------------|------------------|
| Connector Length | 16 mm [.629 in] |
| Connector Height | 12.4 mm [.49 in] |
| PCB Thickness (Recommended) | 1.6 mm [.06 in] |
| Row-to-Row Spacing | 2 mm [.059 in] |

Usage Conditions

| | |
|-----------------------------|-----------------------------|
| Operating Temperature Range | -40 – 105 °C [-40 – 221 °F] |
|-----------------------------|-----------------------------|

Operation/Application

| | |
|---------------------|--------|
| Circuit Application | Signal |
|---------------------|--------|

Industry Standards

| | |
|--------------------|------------|
| UL Rating | Recognized |
| Agency/Standard | UL |
| Approved Standards | UL E28476 |



UL Flammability Rating

UL 94V-0

Packaging Features

Packaging Quantity

450

Packaging Method

Box & Carton

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU

Compliant

EU ELV Directive 2000/53/EC

Compliant

China RoHS 2 Directive MIIT Order No 32, 2016

No Restricted Materials Above Threshold

EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUNE 2023 (235)
Candidate List Declared Against: JUNE 2023 (235)
Does not contain REACH SVHC

Halogen Content

Not Low Halogen - contains Br or Cl > 900 ppm.


Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # CAT-M5833-F3492A
Female-on-Board Connector, Top Entry





TE Part # CAT-M5833-C8684A
Crimp Contacts - Micro-MaTch







TE Part # 1-338070-0
MICRO-MATCH FEM.SE



TE Part # 8-215460-0
MICRO-MATCH FSID P





Also in the Series | Micro-MaTch Industrial



Customers Also Bought





Documents

Product Drawings

MICRO-MATCH COSIHSG

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1-338095-0_D_c-1-338095-0-d.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-338095-0_D_c-1-338095-0-d.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-338095-0_D_c-1-338095-0-d.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Micro-MaTch Catalog

English

Ribbon Cable Interconnect Solutions

English

Datasheet - Ev Charging Board Signal Interconnects

English

Centerline Micro-Match Connector Series

English

Product Specifications

micro-match crimp on snap in male on wire connector

English

Application Specification

English

Product Environmental Compliance

Product Compliance

1-338095-0

Ribbon Cable Connectors, Wire-to-Board, 10 Position, 1.27 mm [.05 in] Centerline, 2 Row, Plug, Standard Profile, Micro-MaTch Industrial



English

[Product Compliance](#)

English

[MATERIAL DECLARATION 1-338095-0](#)

English