

Data sheet | Item number: 261-405

Test plug module; with locking latches; modular; for 4-conductor terminal blocks; for 261 Series; gray

www.wago.com/261-405



Color:

Data

Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Ratings per IEC/EN

Ratings (note)	Maximum test voltage (touch contact): 48 V (test pins are not touch-proof)
Nominal voltage (III/3)	800 V

Ratings per IEC/EN 2

Ratings (note) 2	Maximum test current (touch contact): 0.5 A Maximum test current: 6 A (if the test pins are securely connected in the clamping units)
------------------	--

General information

Test voltage	48 V
Test current	0.5 A

Physical data

Width	10 mm / 0.394 inches
Module width	10 mm / 0.394 inches

Material Data

Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Weight	2.8 g

Environmental requirements

Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data

Product Group	9 (Std Chassis Mt Blocks)
eCl@ss 10.0	27-14-11-48

Subject to changes. Please also observe the further product documentation!



eCl@ss 9.0	27-14-11-48
ETIM 8.0	EC002555
ETIM 7.0	EC002555
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4050821868965
Customs tariff number	85369010000

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	56862e2b-79b8-4032-9d7b-e6f72de30508
SCIP notification number (Belgium)	8851ed8c-18f8-4697-bdca-39505761c979
SCIP notification number (Bulgaria)	858cf710-ee97-4752-862c-1c4882d56357
SCIP notification number (Czech Republic)	4dbaf1df-d3d7-4be8-9120-4c75ddacb0fd
SCIP notification number (Denmark)	ba930414-14ac-43e5-9e01-8a58726a7477
SCIP notification number (Finland)	aff9decb-e211-40b5-b6e0-a07572df4827
SCIP notification number (France)	628f79a4-7667-4e8a-9d76-7890a852bd59
SCIP notification number (Germany)	f98ae75e-aa98-43f1-ba71-6d18c8d1bacf
SCIP notification number (Hungary)	c47ff684-5d98-41f7-b884-4168dff6de2a
SCIP notification number (Italy)	af57ac20-f1b5-4f14-86b8-5f14acff2c49
SCIP notification number (Netherlands)	c7b7caf9-fde1-42d7-a069-3896b78189ad
SCIP notification number (Poland)	a700cfc7-330f-4abb-a8c5-19710f1bee51
SCIP notification number (Romania)	201379da-854c-4274-8bd4-188e9168fbbb
SCIP notification number (Sweden)	c4285ee4-43b1-4bb0-9bb6-0ab374a45360

Optional accessories

Testing and measuring

Testing accessories	
Item no.: 210-136	www.wago.com/210-136
Test plug; 2 mm Ø; with 500 mm cable; red	

Subject to changes. Please also observe the further product documentation!



Downloads

Documentation

Bid Text

261-405 X81 - Datei	2019 年2月19 日	xml 3.2 kB	Download
------------------------	--------------	---------------	----------

261-405 doc - Datei	2017 年8月18 日	doc 25.1 kB	Download
------------------------	--------------	----------------	----------

Additional Information

		pdf 2.2 MB	Download
--	--	---------------	----------

CAD/CAE-Data

CAD data

2D/3D Models 261-405		URL	Download
----------------------	--	-----	----------

CAE data

WSCAD Universe 261-405		URL	Download
------------------------	--	-----	----------

ZUKEN Portal 261-405		URL	Download
----------------------	--	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 261-405 Test plug module; with locking latches; modular; for 4-conductor terminal blocks; for 261 Series; gray		URL	Download
--	--	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Testing after the conductors have been terminated.

Distance between locking devices must be approximately 35 ... 40 mm!

Subject to changes. Please also observe the further product documentation!