

Teashed AntiMigrobial

TECHNICAL DATA SHEET

Part#: 530E-5-USL-050

Cutters - Standoff Shear Small Frame - .050" Standoff - Narrow Jaw Reduces shock on delicate components and solder connections. Long ergonomic cushioned ESD safe handle.

The 530E-5-USL-050 6" narrow anti-shock shear cutter reduces shock on delicate components and solder connections. The "Stand-Off" keeps the cutting blade from cutting into the solder connections. The tip width is .090". It's recommended cutting capacity is 22 AWG (.25" soft wire). It features a soft cushioned ergonomic Anti-Static grip (10¹⁰ ohms/sq surface resistivity) with dual leaf springs.

• Precision Level

Material

Surface Resistivity

Shape

• Type of Cut

Cutting Capacity

Blade Angle

Blade Length

Body Width

• Body Height

OAL

• Weight (OZ)

• UPC

• Schedule B

ECCN

UNSPSC Code

Country of Origin

• Group

Carbon

10¹⁰ ohms/sq

Straight

Shear

.025"

.095"

0.42" (10.5mm)

6" (150mm)

6.2

662847013263


8203.20.60.30

EAR99

27111511

USA

Small Frame



EXCELTA

530E-5-USL Anti-Shock, Standoff Shear Cutter-Long Handle









