

Part Number: PRC-SA-002 (Alternate Part No: S1750U)
Aluminium Housed Proximity Switch - Change Over Contacts
Product Data Sheet

PICTURE



✓ RoHS Compliant


APPLICATIONS INCLUDE

- Position sensing
- Linear actuators
- Security system switch
- Safety guards / devices

FEATURES

- Robust sealed switch, custom housings available.
- Normally open version available.
- Custom cable types, cable lengths, connectors or crimp terminals available.
- Hermetically sealed reed switch for long life.
- Earthed housing for added safety.

DIMENSIONS



Drawings not to scale.
 All dimensions in inches (mm) nominal.

SPECIFICATION

Contact Form / Style	Change-Over	
Switching Voltage	Max. Volts	400 VAC / VDC
Switching Current	Max. Amps	1.0
Switching Capacity	Max. W/VA	60
Carry Current	Max Amps.	2.0
Switching Distance	Make	15 mm (with recommended magnet)
	Break	24 mm (with recommended magnet)
Contact Resistance	Max. mOhms	100
Operating Temperature Range	Celsius	-20°C +85°C
Case Material	Blue powder coated Aluminium	
Cable	4 core 0.75mm ² Black PVC insulated, Br / BI / Bla / G&Y	

As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

Phone: (1) 973 777 6900 **www.comus-intl.com** **Fax: (1) 973 777 8405**

Belgium: + 32 (0)12 390400 - Comus Europe Ltd (Assemblech) UK: +44 (0) 1255 862236 - Germany: +49 (0)911 923 15 943 - Netherlands: +31(0)45 54 39 345 - India: +(91) (44) 43219090
 ©2015 Copyright Comus International, 454 Allwood Road, Clifton NJ 07012, USA