

Power Cords

Power cords for different regions

Features and Benefits

- Provides different plug types for desktop type power adapters



Introduction

The power cords described in this datasheet provide the different plug types used in different regions or countries for desktop type power adapters or Moxa products with AC power inputs.

Appearance

CBL-PJ21NOPEN-BK-30



CBL-PJTB-10



Specifications

Power Parameters

Input Plug Type	<p>PWC-AU Series: Australia plug type PWC-CN Series: China plug type PWC-EU Series: Europe plug type PWC-JP Series: Japan plug type PWC-UK Series: United Kingdom plug type PWC-US Series: United States plug type PWC-AU Series: Australia plug type PWC-CN Series: China plug type PWC-EU Series: Europe plug type PWC-JP Series: Japan plug type PWC-UK Series: United Kingdom plug type PWC-US Series: United States plug type</p>
Input Voltage	<p>JP/US models: 125 VAC AU/CN/EU/UK models: 250 VAC, JP/US models: 125 VAC AU/CN/EU/UK models: 250 VAC</p>
Max. Current	<p>PWC-C13AU-3B-183: 10A PWC-C13AU-3B-183: 10A PWC-C13CN-3B-183: 10A PWC-C13CN-3B-183: 10A PWC-C13EU-3B-183: 10A PWC-C13EU-3B-183: 10A PWC-C13JP-3B-183: 7A PWC-C13JP-3B-183: 7A PWC-C13UK-3B-183: 10A PWC-C13UK-3B-183: 10A PWC-C13US-3B-183: 10A PWC-C13US-3B-183: 10A PWC-C7AU-2B-183: 2.5A PWC-C7AU-2B-183: 2.5A PWC-C7CN-2B-183: 2.5A PWC-C7CN-2B-183: 2.5A PWC-C7EU-2B-183: 2.5A PWC-C7EU-2B-183: 2.5A PWC-C7JP-2B-183: 7A PWC-C7JP-2B-183: 7A PWC-C7UK-2B-183: 2.5A PWC-C7UK-2B-183: 2.5A PWC-C7US-2B-183: 10A PWC-C7US-2B-183: 10A</p>

Physical Characteristics

Thickness	<p>PWC-C13AU-3B-183: 6.3±0.2 mm (0.25±0.01 in) PWC-C13AU-3B-183: 6.3±0.2 mm (0.25±0.01 in) PWC-C13CN-3B-183: 6.3±0.2 mm (0.25±0.01 in) PWC-C13CN-3B-183: 6.3±0.2 mm (0.25±0.01 in) PWC-C13EU-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C13EU-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C13JP-3B-183: 7.0±0.2 mm (0.28±0.01 in) PWC-C13JP-3B-183: 7.0±0.2 mm (0.28±0.01 in) PWC-C13UK-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C13UK-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C13US-3B-183: 6.7±0.2 mm (0.25±0.01 in) PWC-C13US-3B-183: 6.7±0.2 mm (0.25±0.01 in)</p>
Length	<p>PWC-C13 series: 1830±30 mm (72.05±1.18 in) PWC-C7 series: 1830±200 mm (72.05±7.87 in), PWC-C13 series: 1830±30 mm (72.05±1.18 in) PWC-C7 series: 1830±200 mm (72.05±7.87 in)</p>
Cable Length	<p>CBL-PJ21NOPEN-BK-30: 300 ± 20 mm (11.81 ± 0.79 in) CBL-PJ21NOPEN-BK-30: 300 ± 20 mm (11.81 ± 0.79 in) CBL-PJTB-10: 100 ± 20 mm (3.94 ± 0.79 in) CBL-PJTB-10: 100 ± 20 mm (3.94 ± 0.79 in)</p>

Ordering Information

Model Name	Barrel-plug Type	Input-plug Type	Input Voltage
PWC-C13AU-3B-183	–	AU	250 VAC
PWC-C13CN-3B-183	–	CN	250 VAC
PWC-C13EU-3B-183	–	EU	250 VAC
PWC-C13JP-3B-183	–	JP	125 VAC
PWC-C13UK-3B-183	–	UK	250 VAC
PWC-C13US-3B-183	–	US	125 VAC
PWC-C7AU-2B-183	–	AU	250 VAC
PWC-C7CN-2B-183	–	CN	250 VAC
PWC-C7EU-2B-183	–	EU	250 VAC
PWC-C7JP-2B-183	–	JP	125 VAC
PWC-C7UK-2B-183	–	UK	250 VAC
PWC-C7US-2B-183	–	US	125 VAC
CBL-PJ21NOPEN-BK-30	Locking	–	–
CBL-PJTB-10	Non-locking	–	–

© Moxa Inc. All rights reserved. Updated Oct 28, 2021.

This document and any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of Moxa Inc. Product specifications subject to change without notice. Visit our website for the most up-to-date product information.