

FLK 50/EZ-DR/FCN40/100/OMR-IN


Order No.: 2304160

The illustration shows the version FLK 50/EZ-DR/FCN40-OMR/OUT/...



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2304160>

System cable, with a 50-pos. flat-ribbon cable strip and a 40-pos. female connector, cable length: 1 m, for CJ1: ID231, ID261; CS1, C200H: ID111, ID216, ID217; CQM1: ID112, ID213, ID214

| Commercial data | |
|--------------------------|--|
| GTIN (EAN) |  4 017918 927363 |
| Note | Made-to-order |
| sales group | I680 |
| Pack | 1 pcs. |
| Customs tariff | 85444290 |
| Catalog page information | Page 203 (IF-2009) |

Product notes

WEEE/RoHS-compliant since:
06/29/2006



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

| Technical data | |
|---|-----------|
| General | |
| Nominal voltage U_N | < 50 V AC |
| | 60 V DC |
| Max. current carrying capacity per path | 1 A |

| | |
|---|----------------------|
| Max. conductor resistance | 0.16 Ω/m |
| Ambient temperature (operation) | -20 °C ... 50 °C |
| Ambient temperature (storage/transport) | -20 °C ... 50 °C |
| Number of positions, control side | 40 |
| Number of connectors, control side | 1 |
| Number of positions, module side | 50 |
| Number of connectors, modul side | 1 |
| Fixed cable length | 1 m |
| Single wire, cross section | 0.14 mm ² |
| AWG | 26 |
| Conductor construction: Number of litz wires: | 7 |
| Single wire, material | Cu tin-plated |
| External diameter | 10.5 mm |
| Shielding | no |

Certificates / Approvals



Certification

CUL, UL

Address

PHOENIX CONTACT Deutschland GmbH
Flachmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 12000
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact
Technical modifications reserved;