



**Electrical Specifications**

**Center Frequency:** 10100 MHz  
**Bandwidth:** 100 MHz  
**Pass Band:** 10050 – 10150 MHz  
**Insertion Loss:** 1.0 dB Max.  
**Return Loss:** 14 dB Min.  
**Rejection:** ≥ 30 dB @ 9900 MHz  
**Rejection:** ≥ 30 dB @ 10300 MHz  
**Power Handling:** 30 W  
**Impedance:** 50 Ohms


**Mechanical**

**Connector Type:** SMA Female  
**Dimensions:** 3.01" X 0.87" x 0.79" .

**Environmental**

**Operating Temperature:** -55°C to +85°C  
**Storage Temperature:** -55°C to +125°C  
**Shock:** 10 G. 11ms  
**Vibration:** 10 G. 5 to 200Hz

**Outline Drawing:**



Tolerance: +/-0.01 inches [+/- 0.3mm]

Angles: +/- 1 Deg.

\*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.

\*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.




**ANATECH ELECTRONICS INC**  
RF & Microwave Filters & Products

# 10100 MHz Cavity Band Pass Filter

Part Number: AE10100B11647



## Simulation Plot:



Note: This is a simulation Plot. Actual Response plot might differ once product is manufactured.

70 Outwater Lane Phone: (973) 772-4242  
Garfield, NJ 07026 Fax : (973) 321-3941

Email: [sales@anatechelectronics.com](mailto:sales@anatechelectronics.com)  
Web: [www.anatechelectronics.com](http://www.anatechelectronics.com)