



**SPECIFICATIONS**

Mating cycles 500  
 Filter type C  
 Capacitance 470 pF ± 20%  
 Working voltage 100 V  
 Current rating 7,5 A  
 Insulation resistance > 1 GΩ

FREQUENCY (MHz)	ATTENUATION (dB)
5	-
10	1
50	10
100	15
500	35
1000	32

PCB Layout, component side, thickness 1,6 mm

A						Dot. Name		<p>All Dim. in mm Orig. Size DIN A 4</p>	D-Sub, female, angled, 37 poles, turned solder pins, screw locks and brackets with board locks	Maßstab/ Scale  1,5:1																				
				Detail.		08/07/02 CV																								
				Insp.																										
				Stand.																										
<table border="1"> <tr> <td>09 64 414 7225</td> <td>M3</td> </tr> <tr> <td>09 64 414 7224</td> <td>4-40 UNC-2B</td> </tr> <tr> <td>Part number</td> <td>Screw lock thread</td> </tr> </table>			09 64 414 7225	M3	09 64 414 7224	4-40 UNC-2B	Part number	Screw lock thread	<table border="1"> <tr> <td>35300</td> <td>01/12/08</td> <td>PK</td> </tr> <tr> <td>33800</td> <td>16/08/06</td> <td>PK</td> </tr> <tr> <td>31058</td> <td>08/07/02</td> <td>CV</td> </tr> <tr> <td>Mod.</td> <td>Dat.</td> <td>Name</td> </tr> </table>			35300	01/12/08	PK	33800	16/08/06	PK	31058	08/07/02	CV	Mod.	Dat.	Name	HARTING EURL F-95972 Paris				TB 09 64 414 722X		Blatt/ Page 2 / 4
09 64 414 7225	M3																													
09 64 414 7224	4-40 UNC-2B																													
Part number	Screw lock thread																													
35300	01/12/08	PK																												
33800	16/08/06	PK																												
31058	08/07/02	CV																												
Mod.	Dat.	Name																												
							Sub.																							