



GA2K7MCD1 MICRO BetaCHIP (MCD) THERMISTOR PROBES

2K to 100K Ohms Resistance @25°C

0.2°C Tolerance @ 25°C

Thermally Conductive Epoxy Coating

38 AWG Solid Nickel Bifilar with Polyester Type Insulation

Fast Time Response

Small Tip Diameter

RoHS Compliant

Micro BetaCHIP (MCD) thermistor probes are suited for applications that require rapid temperature response and where space is limited. These NTC thermistors are potted in a polyimide tube with a thermally conductive epoxy.

FEATURES


- $\pm 0.2^{\circ}\text{C}$ tolerance @ $+25^{\circ}\text{C}$
- Custom tolerances available
- Smaller than miniature BetaCURVE devices
- Rapid time response (200 milliseconds in liquids)
- Temperature range -40°C to $+125^{\circ}\text{C}$

APPLICATIONS

- Low volume flow sensors (liquids or gases)
- Laboratory animal research
- Peltier temperature tracking sensors
- Temperature control for bath showers
- DNA research sensors
- Medical catheters

GA2K7MCD1
Micro BetaCHIP (MCD) THERMISTOR PROBES

MECHANICAL DETAILS



PERFORMANCE SPECS

Parameters	Units	Value
Nominal Resistance at +25°C	Ohms	2,000
Resistance Tolerance at +25°C	°C	±0.2
Alpha Value at +25°C	%/°C	-3.87
Beta Value 25/85	K	3499
Tolerance on Beta Value 25/85	%	±0.5
Time Response in Liquids	milliseconds	200
Dissipation Constant in Still Air	mW/°C	0.3

GA2K7MCD1
Micro BetaCHIP (MCD) THERMISTOR PROBES

RESISTANCE V TEMPERATURE TABLE DETAILS

Temp. °C	Ohms
-40	43,423.10
-39	40,984.00
-38	38,697.10
-37	36,552.00
-36	34,539.10
-35	32,649.50
-34	30,874.90
-33	29,207.70
-32	27,640.80
-31	26,167.50
-30	24,781.80
-29	23,478.00
-28	22,250.60
-27	21,094.90
-26	20,006.20
-25	18,980.40
-24	18,013.30
-23	17,101.30
-22	16,241.00
-21	15,429.10
-20	14,662.70
-19	13,938.90
-18	13,255.20
-17	12,609.10
-16	11,998.30
-15	11,420.80
-14	10,874.40
-13	10,357.40
-12	9,868.10
-11	9,404.70
-10	8,965.90
-9	8,550.00
-8	8,155.90
-7	7,782.30
-6	7,427.90
-5	7,091.80
-4	6,772.80
-3	6,470.00
-2	6,182.50
-1	5,909.40
0	5,650.00
1	5,403.40
2	5,169.10
3	4,946.20

Temp. °C	Ohms
4	4,734.20
5	4,532.50
6	4,340.50
7	4,157.80
8	3,983.80
9	3,818.00
10	3,660.10
11	3,509.60
12	3,366.20
13	3,229.40
14	3,098.90
15	2,974.40
16	2,855.60
17	2,742.30
18	2,634.00
19	2,530.70
20	2,431.90
21	2,337.60
22	2,247.40
23	2,161.20
24	2,078.80
25	2,000.00
26	1,924.60
27	1,852.50
28	1,783.40
29	1,717.30
30	1,654.00
31	1,593.40
32	1,535.30
33	1,479.70
34	1,426.40
35	1,375.30
36	1,326.20
37	1,279.20
38	1,234.20
39	1,190.90
40	1,149.40
41	1,109.60
42	1,071.30
43	1,034.60
44	999.3
45	965.4
46	932.8
47	901.6

Temp. °C	Ohms
48	871.5
49	842.6
50	814.8
51	788
52	762.3
53	737.5
54	713.7
55	690.8
56	668.7
57	647.4
58	627
59	607.2
60	588.2
61	569.9
62	552.3
63	535.3
64	518.9
65	503.1
66	487.8
67	473.1
68	458.9
69	445.2
70	432
71	419.2
72	406.9
73	395
74	383.5
75	372.4
76	361.7
77	351.4
78	341.3
79	331.7
80	322.3
81	313.3
82	304.5
83	296
84	287.9
85	279.9
86	272.3
87	264.9
88	257.7
89	250.7
90	244
91	237.5

Temp. °C	Ohms
92	231.2
93	225.1
94	219.2
95	213.4
96	207.9
97	202.5
98	197.3
99	192.2
100	187.3
101	182.5
102	177.9
103	173.4
104	169.1
105	164.9
106	160.8
107	156.8
108	153
109	149.2
110	145.6
111	142.1
112	138.6
113	135.3
114	132.1
115	128.9
116	125.9
117	122.9
118	120
119	117.2
120	114.5
121	111.9
122	109.3
123	106.8
124	104.4
125	102

GA2K7MCD1
Micro BetaCHIP (MCD) THERMISTOR PROBES

ORDERING INFORMATION

Part Number	Description	Ω @25°C	MOQ*
GA2K7MCD1	Micro BetaCHIP thermistor probe (MCD)	2,000	1,000

* For quantities less than MOQ (Minimum Order Quantity) contact distribution

NORTH AMERICA
Tel +1 800 522 6752
customer-care.ando@te.com

EUROPE
Tel +31 73 624 6999
customer-care.glwy@te.com

ASIA
Tel +86 0400 820 6015
customer-care.chdu@te.com

te.com/sensorsolutions

BetaCURVE, BetaCHIP, TE Connectivity, TE, and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, products and/or company names referred to herein may be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

© 2018 TE Connectivity Ltd. family of companies All Rights Reserved.