

In case of consideration for using Autom otive equipm ent/device which dem and high reliability, kindly contact our sales w indow correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		QT	AT	
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C ⁽¹⁾		STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C ⁽²⁾			
	VOLTAGE	50 V AC		OPERATING HUMIDITY RANGE	RELATIVE HUMIDITY 95 % RH MAX. ⁽³⁾			
	CURRENT	0.3 A		STORAGE HUMIDITY RANGE	40 % TO 70 % ⁽²⁾			
SPECIFICATIONS								
ITEM	TEST METHOD			REQUIREMENTS			QT	AT
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.			x	x
MARKING		CONFIRMED VISUALLY.					x	x
ELECTRIC CHARACTERISTICS								
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).		60 m Ω MAX.		x	-	
INSULATION RESISTANCE		100 V DC		100 M Ω MIN.		x	-	
VOLTAGE PROOF		150 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.			x	x
MECHANICAL CHARACTERISTICS								
INSERTION AND WITHDRAWAL FORCE		MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE: 57.6 N MAX. WITHDRAWAL FORCE: 2.4 N MIN.		x	-	
MECHANICAL OPERATION		50 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 70 m Ω MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x	-	
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE : 0.75 mm, AT 10 CYCLES FOR 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μ s. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x	-	
SHOCK		490 m/s ² , DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				x	-	
ENVIRONMENTAL CHARACTERISTICS								
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 \pm 2 °C, 90 ~ 95 %, 96 h.		① CONTACT RESISTANCE: 70 m Ω MAX. ② INSULATION RESISTANCE: 100 M Ω MIN. ③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x	-	
RAPID CHANGE OF TEMPERATURE		TEMPERATURE: -55 \rightarrow +15 \rightarrow +35 \rightarrow +85 \rightarrow +15 \rightarrow +35 °C TIME 30 \rightarrow 2 ~ 3 \rightarrow 30 \rightarrow 2 ~ 3 min. UNDER 5 CYCLES.				x	-	
DRY HEAT		EXPOSED AT 85 °C, 96h.		① CONTACT RESISTANCE: 70 m Ω MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		x	-	
COLD		EXPOSED AT -55 °C, 96h.				x	-	
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.		① CONTACT RESISTANCE: 70 m Ω MAX. ② NO HEAVY CORROSION.		x	-	
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JIS C 0090)				x	-	
RESISTANCE TO SOLDERING HEAT		1) REFLOW SOLDERING: 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINAL.		x	-	
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, 240 °C, FOR IMMERSION DURATION, 3 s.		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.		x	-	
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED		DATE		
REMARK ⁽¹⁾ TEMPERATURE RISE INCLUDED WHEN ENERGIZED. ⁽²⁾ THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. ⁽³⁾ NO DEW CONDENSATION IS PERMITTED.								
Unless otherwise specified, refer to JIS C 5402.				DRAWING NO.		ELC4-151952-25		
Note QT: Qualification Test AT: Assurance Test X: Applicable Test								
HRS		SPECIFICATION SHEET		PART NO.		FX10A-96P-SV (71)		
		HIROSE ELECTRIC CO., LTD.		CODE NO.		CL570-0041-0-71		
				APPROVED		HS. OKAWA		
				CHECKED		HT. YAMAGUCHI		
		DESIGNED		SY. KAMIIGA		08.07.22		
		DRAWN		HK. SUWADORI		08.07.22		