



- NOTES:
1. MATERIALS: HOUSING - LIQUID CRYSTAL POLYMER (LCP), GLASS-FILLED, UL94V-0
TERMINALS - HIGH PERFORMANCE COPPER ALLOY
 2. FINISH: 30µN MIN GOLD IN CONTACT AREA, SELECTIVE TIN ON PCB TAILS, NICKEL OVERALL.
 3. REFER TO MOLEX PRODUCT SPEC PS-76060-999 FOR PERFORMANCE SPECIFICATIONS AND ADDITIONAL PCB INFORMATION.
 4. EACH SIGNAL WAFER CONTAINS 2 COLUMNS OF TERMINALS.
 5. PRODUCT IS PACKAGED PER PK-70873-589.
 6. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPEC PS-45499-002.
 7. REFER TO MOLEX SALES DRAWING SD-76145-003 FOR THE MATING HEADERS AND SD-76560-004 FOR THE MATING RAM CONNECTORS.
 8. REFER TO MOLEX PCB ROUTING GUIDE AS-76060-990 FOR ANTIPAD AND ROUTING RECOMMENDATIONS.
 9. PART NUMBER 76150-5120 SHOWN ON DRAWING. KEY FEATURES WILL CHANGE WITH COLUMN SIZE
 10. MINIMUM BOARD THICKNESS IS 1.00 mm FOR COMPLIANT PIN FUNCTIONALITY.
 11. WHEN USING MOLEX SUPPLIED #2-32 SCREW 73726-0000 (9.50mm ±0.38 THREADABLE SCREW LENGTH), THE MAXIMUM BOARD THICKNESS IS 4.4mm.
 12. MARKING: LOCATED APPROXIMATELY AS SHOWN. PART NUMBER AND DATE CODE.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: MIGRATED TO NX	
mm	NTS		
GENERAL TOLERANCES (UNLESS SPECIFIED)			
ANGULAR TOL	± 0.5°	EC NO: 622829	
4 PLACES	±	DRWN: PKH	2019/08/22
3 PLACES	±	CHK'D: BOKOK	2019/08/29
2 PLACES	± 0.13	APPR: SHONG	2019/08/30
1 PLACE	± 0.25	INITIAL REVISION:	
0 PLACES	±	DRWN: MCARRANZA	2007/06/12
		APPR: JLAURX	2008/04/24
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING SERIES
			C-SIZE 76150
DOCUMENT STATUS		DOCUMENT NUMBER	
P1	RELEASE DATE	SD-76150-004	
	2019/08/30 15:04:21	DOC TYPE DOC PART REVISION	
		PSD	001 H3
		SHEET NUMBER	
		1 OF 2	

molex

IMPACT 100 OHM DC
6 PAIR SIGNAL MODULE GUIDE RIGHT SALES DWG

PRODUCT CUSTOMER DRAWING

MATERIAL NUMBER	# OF COLUMNS	# OF DIFF PAIR	DIM "A" MAX	DIM "B"	PTH \varnothing
76150-**10	10	60	26.60	17.10	0.46 \pm 0.05
76150-**14	14	84	34.20	24.70	
76150-**16	16	96	38.00	28.50	
76150-**20	10	60	26.60	17.10	0.39 \pm 0.05
76150-**24	14	84	34.20	24.70	
76150-**26	16	96	38.00	28.50	

76150-*** **

5 = RIGHT GUIDED LEAD-FREE

OF COLUMNS

POLARIZATION KEY ORIENTATION

0 = NO KEY

1 = A 5 = E
 2 = B 6 = F
 3 = C 7 = G
 4 = D 8 = H

10 = 10 COL 0.46 PTH
 14 = 14 COL 0.46 PTH
 16 = 16 COL 0.46 PTH
 20 = 10 COL 0.39 PTH
 24 = 14 COL 0.39 PTH
 26 = 16 COL 0.39 PTH

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: MIGRATED TO NX		molex			
mm	NTS						
GENERAL TOLERANCES (UNLESS SPECIFIED)		EC NO: 622829		IMPACT 100 OHM DC 6 PAIR SIGNAL MODULE GUIDE RIGHT SALES DWG			
ANGULAR TOL	\pm 0.5°	DRWN: PKH	2019/08/22				
4 PLACES	\pm	CHK'D: BOKOK	2019/08/29	PRODUCT CUSTOMER DRAWING			
3 PLACES	\pm	APPR: SHONG	2019/08/30				
2 PLACES	\pm 0.13	INITIAL REVISION:		DOCUMENT NUMBER			
1 PLACE	\pm 0.25	DRWN: MCARRANZA	2007/06/12				SD-76150-004
0 PLACES	\pm	APPR: JLAURX	2008/04/24	DOC TYPE	DOC PART	REVISION	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
			C-SIZE	76150	SEE CHART	GENERAL MARKET	2 OF 2

DOCUMENT STATUS	P1	RELEASE DATE	2019/08/30	15:04:21
-----------------	----	--------------	------------	----------