
TE Internal #: 2-2273127-4 M12 Cable Assembly, 5 Position, 1.5 m, Sensor/Actuator, Code A, M12 Socket, M12 Plug, Double Ended, Plastic

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M12 A-Code Male Straight to Female LED Double Ended Cable



M8/M12 Application Type: Sensor/Actuator

Number of Positions: 5

Connector & Keying Code: A

Connector Type (End A): M12 Socket
Connector Type (End B): M12 Plug

All M12 A-Code Male Straight to Female LED Double Ended Cable (60)

#### **Features**

### **Product Type Features**

Connector Type (End A)	M12 Socket
Connector Type (End B)	M12 Plug
Cable Assembly Type	M12
Configuration Features	
Status Indicator Type	LED
Number of Positions	5
Electrical Characteristics	
Operating Voltage	24 VDC
Body Features	
Cable Color	Black
Connector Color (End B)	Black
Connector Color (End A)	Black
Jacket Material	PUR, PVC



Wire Color (Base)	Brown, White, Blue, Black, Gray		
Connector & Keying Code	A		
Contact Features			
Contact Current Rating (Max)	4 A		
Mechanical Attachment			
Thread Size	M12 x M12		
Connector Orientation (End A)	Right Angle		
Connector Orientation (End B)	Straight		
Housing Features			
Housing Material	Plastic		
Dimensions			
Outside Cable Diameter	5.9 mm[.23 in]		
Wire Size	.326 mm²		
Usage Conditions			
Operating Temperature Range	-30 - 80 °C[-22 - 176 °F]		
Operation/Application			
M8/M12 Application Type	Sensor/Actuator		
Shielded	No		
Packaging Features			
Packaging Quantity	25		
Packaging Method	Box		
Other			
Field Serviceable	Yes		
Cable Assembly Length	1.5 m		
Cable Assembly Configuration	Double Ended		

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	



Current ECHA	Candidate	List:	JUNE	2023

(235)

Candidate List Declared Against: JUL 2021

(219)

Does not contain REACH SVHC

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



# **Customers Also Bought**





#### **Documents**

**Product Drawings** 

M12 angld sckt to M12 strght plg 3 LED



English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2-2273127-4\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-2273127-4\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2-2273127-4\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

M8 / M12 Connector System Catalog

Japanese

**Product Specifications** 

**Product Specification** 

English