

Lots of installers use tape, butyl, and more tape which is incredibly time consuming and difficult to do when you have connections/cables close to one another. Our Magic Tape seeks to make this process a bit easier as the Ethylene Propylene Rubber (or EPR) material used in our tape adheres to itself without glue. For that reason, it is sometimes referred to as “Cold Shrink Tape.” You won’t find a better option than our magic tape.



Gamma’s Magic Tape removes the need for adhesives and makes it possible to weatherproof those incredibly difficult areas where solutions like Cold Shrink or Slide-On Boots aren’t an option. Magic Tape can also be used for short-term repairs and is a great option to keep in your bag because you never know when you’ll need it.



### Characteristics

- Easily Removed with Knife
- Colors: Black
- Highly Flexible
- Rated to 69kv
- Excellent Tear Resistance
- Acid and Alkalis Resistant
- Recommended Installation Temperature: -15° F to 135° F
- Operating Temperature -40° F to 230° F
- Perfect Application for Remote Radio Unit Connections
- Protect Connectors from Weather, Moisture, UV, Ozone, Dust and Fungus

Properties	Test Method	Values
Thickness	ASTM D4325	0.76mm
Tensile Strength	ASTM D 4325	3.0 Mpa
Elongation at Break	ASTM D 4325	800%
Fusion	ASTM D4388	Pass
Ozone Resistance	ASTM D4388	Pass
UV Resistance	ASTM D4388	Pass
Dielectric Strength	ASTM D149:64	36KV/mm
Dielectric Constant	ASTM D150:74	2.8
Volume Resistivity	ASTM D150:74	$\geq 5 \times 10^{14} \Omega \cdot \text{cm}$
Water Absorption	ASTM D570:63	0.05% (24hrs)
Corrosion Liability	BS3924:78	None

Ordering Information			
Part Number	Width	Thickness	Length
TSSA-1.5-.76-15	1.5 INCHES	.76 mm	15 FT

Size	Connections Per Roll
1/2" to 1/2"	3
1/2" to 7/8"	2
1/2" to 1-1/4"	1
1/2" to 1-5/8"	1



**Property of Gamma Electronics Inc.**

2818 Metropolitan Place, Suite A  
 Pomona, CA 91767  
[www.gammaelectronics.net](http://www.gammaelectronics.net)