

1

2

3

4

5

TECHNICAL CHARACTERISTICS

MATERIAL  
COLOR: BLACK  
STYLE: UL1007

ENVIRONMENTAL  
OPERATING TEMPERATURE: -20°C UP TO 80°C  
COMPLIANCE: LEAD FREE AND ROHS

WIRE DIMENSION  
AWG: 30

PACKAGING  
10 PCS/BAG


A

B

C

D

Terminal A




3 mm Pre-stripped



Terminal B

Wire Length 150mm ±5



Terminal A	662 004 137 22
Terminal B	Pre-stripped

RoHS Compliant

G			
F			
E			
D			
C			
B			
A	24-NOV-15	PDF	AK
REV	DATE	FILE	BY

PROJECTION:

GENERAL TOLERANCE  
.X = +/- 0.2  
.XX = +/- 0.15



APPROVAL: BBu

UNIT: MM  
SCALE:  
SHEET: 1/2  
DRAW: AK

DESCRIPTION: WR-MPC3 3.00 MM FEMALE PRE-CRIMPED CABLE  
WERI PART NO: 662 400 130 015

SIZE  
**A4**

1

2

3

4

5

## Cautions and Warnings:

This electronic component is designed and developed with the intention for use in general electronics equipments.



Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Würth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

A

B

C

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = +/- 0.2 .XX = +/- 0.15		DESCRIPTION: DISCLAIMER	SIZE <b>A4</b>
G								
F								
E								
D				APPROVAL: JC	UNIT: MM	WERI PART NO: DISCLAIMER	SIZE <b>A4</b>	
C					SCALE:			
B					SHEET: 2/2			
A	10-SEP-14	PDF	QL		DRAW: QL			
REV	DATE	FILE	BY					

D