
EU Power Cord with IEC Appliance Connector C19, V-Lock





V-Lock C19 Connector

Power plug EU black



Description

- Power Cord

- Protection class I , Pin temperature 70 $^{\circ}\mathrm{C}$

with V-Lock interlocking system

See below: Approvals and Compliances

Weblinks

pdf data sheet, html datasheet, General Product Information, Approvals, CE declaration of conformity, Distributor-Stock-Check, Accessories, Detailed request for product

Technical Data			
Ratings IEC	16A / 250 VAC; 50/60 Hz	Appliance inlet/-outlet	C19 acc. to IEC 60320-3
Dielectric Strength	> 2 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50 Hz)		(for cold conditions) pin-temperature 70 °C, 16A, Protection Class I
Allowable Operation Tempe- rature	-25 °C to 70 °C		
IP-Protection	front side IP20 acc. to IEC 60529		
Protection against electric shock	Suitable for appliances with protection class I acc. to IEC 61140		
Terminal	moulded		
Material: Housing	PVC, black		

Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: 6051.2103

Approval Logo	Certificates	Certification Body	Description
	VDE Approvals	VDE	VDE Certificate Number:
\mathbb{N}	NEMKO Approvals	NEMKO	Norges Elektriske Materiellkontroll
S	SEMKO Approvals	SEMKO	Svenska Elektriska Materielkontrollanstalten
	DEMKO Approvals	DEMKO	Denmark s Electrical Equipment Control (DEMKO)
(F)	FIMKO Approvals	FIMKO	Finnish Electrical Inspectorate
(B)	IMQ Approvals	IMQ	Italian power cable products with IMQ certification are designed according to CEI 23-16 and IEC standards for Italian power cable applications.
Keur	KEMA Approvals	KEMA	Testing of electrotechnical materials
OVE	OEVE Approvals	OEVE	Austrian Electrotechnical Association OVE

6051.2103

Product standards

Product standards that are referenced

Organization	Design	Standard	Description					
IEC	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes					
IEC	Designed according to	IEC 60320-3	Appliance couplers for household and similar general purposes					
(AJA)	Designed according to	IEC 60320-1	Appliance couplers for household and similar general purposes					
(AJA)	Designed according to	BS 1363-1	Socket-outlets, adapters and connection units					

Application standards

Application standards where the product can be used

Organization	Design	Standard	Description
IEC.	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements

Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
CE	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.
√ -Lock		SCHURTER AG	V-Lock system are based on a matching plug-dose combination. The connector is equipped with a notch intended for use with the latching cordset. The cord latching system prevents against accidental removal of the cordset.

All Variants

Connec	Connector Cable				Plug				Order Number		
Туре	V-Lock	Cord Type	Conductor cross section	Length [m]	Color	Туре	Country	Standard	Style		
C19	•	H05VV- F3G1.5	3 x 1.5 mm ²	3.0	black	Europlug	EU	CEE 7 / VII	angled	-	6051.2103

Most Popular.

Availability for all products can be searched real-time:https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER

Packaging unit

30 Pcs