

Datasheet revision 1.4 www.chipquik.com

# Liquid Flux Alcohol-Based No-Clean in 10ml (0.34oz) Pen w/tip

## **Product Highlights**

No-Clean Low solids Alcohol-Based

Ideal for all rework, solder, and de-solder applications

Excellent wetting

Easily cleaned with isopropyl alcohol (IPA)

Can be used with Leaded and Lead-Free applications

**RoHS 3 and REACH compliant** 



Flux Type: No-Clean Liquid (for Leaded and Lead-Free applications)

Flux Classification: ORL0
Specific Gravity: 0.8
Packaging: 10ml Pen

Shelf Life: Refrigerated >24 months, Unrefrigerated >24 months

### **Dispensing**

Gently press tip into work piece (depress tip) to dispense.

## **Storage and Handling**

Store refrigerated or at room temperature 3-25°C (37-77°F). The liquid flux can be allowed to freeze. Freezing will not degrade this product. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

#### **Transportation**

This product requires ground shipping. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground will not impact this product's stated shelf life.

#### **Cleaning**

This is a no-clean liquid flux, post-use cleaning is not required. If cleaning is desired, residue can be cleaned with isopropyl alcohol (IPA), or most other alcohol-based solvent flux removers.

#### **Conforms to the following Industry Standards:**

J-STD-004B, Amendment 1 (Solder Fluxes):

Yes

RoHS 3 Directive 2015/863/EU:

Yes