

In case of consideration for using Autom otive equipm ent/device which dem and high reliability, kindly contactour sales w indow correspondents.

APPLICABLE STANDARD		TEST METHOD		REQUIREMENTS		Q/T	AT
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C (1)	STORAGE TEMPERATURE RANGE	-10 °C TO 60 °C (2)			
	VOLTAGE	100 V AC	OPERATING HUMIDITY RANGE	40 % TO 80 %			
	CURRENT	0.5 A	STORAGE HUMIDITY RANGE	40 % TO 70 % (2)			
<b>SPECIFICATIONS</b>							
ITEM	TEST METHOD		REQUIREMENTS		Q/T	AT	
<b>CONSTRUCTION</b>							
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X	X	
MARKING	CONFIRMED VISUALLY.				X	X	
<b>ELECTRIC CHARACTERISTICS</b>							
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).		40 mΩ MAX.		X	-	
CONTACT RESISTANCE	20 mV MAX, 1 mA(DC OR 1000Hz)		50 mΩ MAX.		X	-	
MILLIVOLT LEVEL METHOD							
INSULATION RESISTANCE	250 V DC		100 MΩ MIN.		X	-	
VOLTAGE PROOF	300 V AC FOR 1 min.		NO FLASHOVER OR BREAKDOWN.		X	-	
<b>MECHANICAL CHARACTERISTICS</b>							
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.		① CONTACT RESISTANCE: 50 mΩ MAX.		X	-	
			② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
VIBRATION	FREQUENCY 10 TO 55 Hz. AMPLITUDE : 1.5 mm. 2 hrs IN 3 DIRECTIONS.		① NO ELECTRICAL DISCONTINUITY OF 1 μs.		X	-	
SHOCK	490 m/s <sup>2</sup> , DURATION OF PULSE 11 ms FOR 3 TIMES IN 3 DIRECTIONS.		② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-	
<b>ENVIRONMENTAL CHARACTERISTICS</b>							
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 hrs.		① CONTACT RESISTANCE: 50 mΩ MAX.		X	-	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE:-55→+15~+35→ +85→+15~+35°C TIME 30 → MAX 5 → 30 → MAX 5 min 5 CYCLES.		② INSULATION RESISTANCE: 100 MΩ MIN.		X	-	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 hrs.		③ NO DAMAGE, CRACK AND LOOSENESS OF PARTS.				
HYDROGEN SULPHIDE	EXPOSED IN 3 PPM FOR 96 hrs. (TEST STANDARD: JEIDA 38)		① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.		X	-	
RESISTANCE TO SOLDERING HEAT	1) REFLOW SOLDERING : 250 °C MAX, : 220 °C MIN, FOR 60 s 2) SOLDERING IRONS : 360 °C, FOR 5 s		NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		X	-	
SOLDERABILITY	SOLDERED AT SOLDER TEMPERATURE: 240°C, FOR IMMERSION DURATION, 3 sec.		A NEW UNIFORM COATING OF SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMERSERD.		X	-	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE			
△							
<b>REMARK</b> (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED. (2) THIS STORAGE INDICATES A LONG-TERM STORAGE STATE FOR THE UNUSED PRODUCT BEFORE THE BOARD MOUNTED. Unless otherwise specified, refer to MIL-STD-1344.							
Note Q1: Qualification Test AT: Assurance Test X: Applicable Test		DRAWING NO.	ELC4-071331-25				
<b>HRS</b> SPECIFICATION SHEET HIROSE ELECTRIC CO., LTD.		PART NO.	FX6A-80P-0.8SV2 (71)				
		CODE NO.	CL576-0247-3-71				