

Data sheet | Item number: 753-421

2-channel digital input; 24 VDC; 3 ms; Diagnostics

www.wago.com/753-421



Color:



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

This digital input module receives control signals from the field side and supplies a short-circuit proof voltage to the sensors. The module transfers the control signals and other information via a fieldbus coupler to the higher-level controller.

Each input module has a noise-rejection filter.

Each sensor can be supplied separately. A short circuit to ground is indicated as an error/fieldbus failure and a message is sent to the supervisory control.

The error is canceled automatically after it has been rectified.

Field and system levels are electrically isolated.

Subject to changes. Please also observe the further product documentation!



Data Notes

| | |
|------|------------------------------------------------------------------------|
| Note | Pluggable connectors and coding fingers (753 Series) are not included. |
|------|------------------------------------------------------------------------|

Technical data

| | |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Number of digital inputs | 2 |
| Total number of channels (module) | 2 |
| Signal type | Digital |
| Signal type (voltage) | 24 VDC |
| Sensor connection | 2 x (2-wire, 3-wire) |
| Input characteristic | high-side switching |
| Input filter (digital) | 3 ms |
| Input current per channel for signal (1) typ. | 3.7 mA |
| Output current per channel | 0.5 A |
| Short-circuit current | 1.5 A, pulsating due to thermal overload protection |
| Voltage range for signal (0) | -3 ... +5 VDC |
| Voltage range for signal (1) | 15 ... 30 VDC |
| Diagnostics | Short circuit, automatic acknowledgment after error rectified |
| Input data width (internal) max. | 4 bits |
| Supply voltage (system) | 5 VDC; via data contacts |
| Current consumption (5 V system supply) | 12 mA |
| Supply voltage (field) | 24 VDC (-25 ... +30 %); via power jumper contacts (power supply via blade contact; transmission via spring contact) |
| Isolation | 500 V system/field |
| Indicators | LED (A, C) green: Status DI 1, DI 2; LED (B, D) red: Error DI 1, DI 2 |
| Number of incoming power jumper contacts | 2 |
| Number of outgoing power jumper contacts | 2 |
| Current carrying capacity (power jumper contacts) | 10 A |

Connection data

| | |
|---------------------------------------|-----------------|
| Connection technology: inputs/outputs | 8 x CAGE CLAMP® |
| Connection type 1 | Inputs/outputs |

Subject to changes. Please also observe the further product documentation!



| | |
|-------------------------|----------------------------------------------|
| Solid conductor | 0.08 ... 2.5 mm ² / 28 ... 14 AWG |
| Fine-stranded conductor | 0.08 ... 2.5 mm ² / 28 ... 14 AWG |
| Strip length | 9 ... 10 mm / 0.35 ... 0.39 inches |

Physical data

| | |
|-----------------------------------|------------------------|
| Width | 12 mm / 0.472 inches |
| Height | 100 mm / 3.937 inches |
| Depth | 69.8 mm / 2.748 inches |
| Depth from upper-edge of DIN-rail | 62.6 mm / 2.465 inches |

Mechanical Data

| | |
|---------------------|-------------|
| Mounting type | DIN-35 rail |
| Pluggable connector | pluggable |

Material Data

| | |
|--------------------|------------------------------|
| Color | light gray |
| Housing material | Polycarbonate; polyamide 6.6 |
| Fire load | 1.144 MJ |
| Weight | 41 g |
| Conformity marking | CE |

Environmental requirements

| | |
|------------------------------------------------------------------------------------|---------------------------------------|
| Ambient temperature (operation) | 0 ... +55 °C |
| Ambient temperature (storage) | -40 ... +85 °C |
| Protection type | IP20 |
| Pollution degree | 2 per IEC 61131-2 |
| Operating altitude | 0 ... 2000 m / 0 ... 6562 ft |
| Mounting position | horizontal (standing/lying); vertical |
| Relative humidity (without condensation) | 95 % |
| Vibration resistance | 4g per IEC 60068-2-6 |
| Shock resistance | 15g per IEC 60068-2-27 |
| EMC immunity to interference | per EN 61000-6-2, marine applications |
| EMC emission of interference | per EN 61000-6-4, marine applications |
| Exposure to pollutants | per IEC 60068-2-42 and IEC 60068-2-43 |
| Permissible H ₂ S contaminant concentration at a relative humidity 75 % | 10 ppm |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Permissible SO₂ contaminant concentration at a relative humidity 75 % 25 ppm

Commercial data

| | |
|-----------------------|-----------------|
| Product Group | 15 (I/O System) |
| eCl@ss 10.0 | 27-24-26-04 |
| eCl@ss 9.0 | 27-24-26-04 |
| ETIM 8.0 | EC001599 |
| ETIM 7.0 | EC001599 |
| Recupel Type | |
| PU (SPU) | 1 pcs |
| Packaging type | Box |
| Country of origin | DE |
| GTIN | 4044918937368 |
| Customs tariff number | 85389099990 |

Environmental Product Compliance

| | |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| CAS-No. | 1303-86-2 1317-36-8 25550-51-0 7439-92-1 79-94-7 |
| REACH Candidate List Substance | 2,2',6,6'-tetrabromo-4,4'-isopropylidenediphenol 4-Methyl-1,2-cyclohexanedicarboxylic anhydride Diboron trioxide Lead Lead monoxide |
| RoHS Compliance Status | Compliant,With Exemption |
| RoHS Exemption | 6(c) 7(a) 7(c)-I 7(c)-II |
| SCIP notification number (Austria) | 690e68ba-0215-4460-892c-37fe1829a6b1 |
| SCIP notification number (Belgium) | cf312aab-40e3-4b6c-b284-ee7b8f7cef5f |
| SCIP notification number (Bulgaria) | 7f7d90a1-0037-474b-a8d3-a13bf4d4cf00 |
| SCIP notification number (Czech Republic) | a7a51d37-4553-436b-ac5a-63f90fdf4fcd |
| SCIP notification number (Denmark) | a229da12-194d-4141-bede-a5fe05bf6cab |
| SCIP notification number (Finland) | 27fcb888-d74f-47ae-9161-7cd7fe5d1be0 |
| SCIP notification number (France) | 40a1933a-aeab-4ad4-b91f-bc1a224396aa |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



| | |
|----------------------------------------|--------------------------------------|
| SCIP notification number (Germany) | 1942a76c-07f2-4c7b-bc76-6d8511c51d0a |
| SCIP notification number (Hungary) | 0fe759e0-a668-450a-8913-82771fc353e3 |
| SCIP notification number (Italy) | 02316f18-8b6f-4a97-929f-eead91b15d67 |
| SCIP notification number (Netherlands) | 70f31585-0b8b-4257-9085-87e58bd25220 |
| SCIP notification number (Poland) | 5a2089cc-2114-45c3-9131-56013a523618 |
| SCIP notification number (Romania) | f68942ba-b137-4184-b692-7239718335af |
| SCIP notification number (Sweden) | 949b3597-e3c1-4e64-855f-c7b79c985c0a |

Approvals / Certificates

General approvals

| Logo | Approval | Additional Approval Text | Certificate name |
|------|------------------------------------------------------------------|--------------------------|-------------------------------------|
| | EAC Brjansker Zertifizierungsstelle | TP TC 020/2011 | EAC RU C-DE.AM02. B.00087 /19 |
| | KC National Radio Research Agency | Article 58-2, Clause 3 | MSIP-REM-W43-DIM750 |
| | UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS) | UL 508 | E175199 Sec.1 |

Declarations of conformity and manufacturer's declarations

| Logo | Approval | Additional Approval Text | Certificate name |
|------|-----------------------------------------------------------|--------------------------|------------------|
| | EU-Declaration of Conformity WAGO GmbH & Co. KG | - | - |
| | UK-Declaration of Conformity WAGO GmbH & Co. KG | - | - |

Approvals for marine applications

| Logo | Approval | Additional Approval Text | Certificate name |
|------|--------------------------------------------------------------|--------------------------|-------------------|
| | ABS American Bureau of Shipping | - | 22-2219060 |
| | BSH Bundesamt fuer Seeschifffahrt und Hydrographie | - | 1104 |
| | BV Bureau Veritas S.A. | - | 13453/E0 BV |
| | DNV DNV GL SE | DNV-CG-0339, Aug. 2021 | TAA0000194 |
| | KR Korean Register of Shipping | - | KR HMB05880-AC001 |

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



| | | |
|--------------------------------------|---|-----------------------|
| LR Lloyds Register EMEA | - | LR22180952TA |
| PRS Polski Rejestr Statków | - | TE/2236/880590 /19 |
| RINA RINA Germany GmbH | - | ELE343521XG001 |

Approvals for hazardous areas

| Logo | Approval | Additional Approval Text | Certificate name |
|----------------------------------------------------------------------|----------|--------------------------|------------------------------------------------------|
| ATEX TUEV Nord Cert GmbH | | EN 60079-0 | TUEV14ATEX148929X (II 3 G Ex ec IIC T4 Gc) |
| CCCEX CQST/CNEX | | CNCA-C23-01 | 2020312310000213 (Ex ec IIC T4 Gc) |
| EAC Brjansker Zertifizierungsstelle | | TP TC 012/2011 | EAC RU C-DE.AM02.B.00163 /19 (2Ex nA IIC T4 Gc X) |
| IECEX TUEV Nord Cert GmbH | | IEC 60079-0 | IECEX TUN 14.0035 X (Ex ec IIC T4 Gc) |
| INMETRO TÜV Rheinland do Brasil Ltda. | | IEC 60079-0 | BR-Ex_TÜV 12.1297 X |
| UKEx WAGO GmbH & Co. KG | | EN 60079-0 | UKCA_WAGO22UKEX003X_ec |
| UL Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS) | | UL 121201 | E198726 Sec.1 |

Required accessories**Pluggable connector**

| Male connector/plug | | |
|----------------------------------|--|----------------------------------------------------------------|
| Item no.: 753-110 Plug | | www.wago.com/753-110 |

Optional accessories**Carrier rail**

| Mounting accessories | | |
|----------------------------------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------|
| Item no.: 210-197 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715; silver-colored | | www.wago.com/210-197 |
| Item no.: 210-198 Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored | | www.wago.com/210-198 |
| Item no.: 210-504 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715; silver- | | www.wago.com/210-504 |

Subject to changes. Please also observe the further product documentation!



colored

Item no.: 210-505

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715; silver-colored

www.wago.com/210-505**Item no.: 210-506**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715; silver-colored

www.wago.com/210-506**Item no.: 210-508**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715; silver-colored

www.wago.com/210-508**Item no.: 210-113**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored

www.wago.com/210-113**Item no.: 210-118**

Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; silver-colored

www.wago.com/210-118**Item no.: 210-112**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm; silver-colored

www.wago.com/210-112**Item no.: 210-114**

Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

www.wago.com/210-114**Item no.: 210-115**

Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm; silver-colored

www.wago.com/210-115**Item no.: 210-196**

Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored

www.wago.com/210-196**System housing**

System enclosure

Item no.: 850-814/002-000

IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate

www.wago.com/850-814/002-000**Item no.: 850-815/002-000**

IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate

www.wago.com/850-815/002-000**Item no.: 850-816/002-000**

IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate

www.wago.com/850-816/002-000**Item no.: 850-817/002-000**

IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate

www.wago.com/850-817/002-000**Item no.: 850-825**

IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20

www.wago.com/850-825**Item no.: 850-826**

IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable

www.wago.com/850-826

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



grip

Item no.: 850-827

IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip

www.wago.com/850-827**Item no.: 850-827/002-000**

IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip

www.wago.com/850-827/002-000**Item no.: 850-826/002-000**

IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip

www.wago.com/850-826/002-000**Item no.: 850-828/002-000**

IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip

www.wago.com/850-828/002-000**Item no.: 850-828**

IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip

www.wago.com/850-828**Item no.: 850-834**

IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20

www.wago.com/850-834**Item no.: 850-835**

IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip

www.wago.com/850-835**Item no.: 850-836**

IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip

www.wago.com/850-836**Shield termination**

Shield clamping saddles

Item no.: 790-116

Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm

www.wago.com/790-116**Item no.: 790-124**

Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm

www.wago.com/790-124**Item no.: 790-108**

Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm

www.wago.com/790-108**Item no.: 790-140**

Shield clamping saddle; diameter of compatible conductor

www.wago.com/790-140**Item no.: 790-216**

Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm

www.wago.com/790-216**Item no.: 790-220**

Shield clamping saddle; 30 mm wide; 6 ... 20 mm

www.wago.com/790-220**Item no.: 790-208**

Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm

www.wago.com/790-208**Marking accessories**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



| | | |
|--------------------------------------------------------------------------------------------------------------|--|----------------------------------------------------------------------------------|
| Marker carrier | | |
| Item no.: 750-103 | | www.wago.com/750-103 |
| Group marker carrier | | |
| Marker | | |
| Item no.: 2009-145/000-006 | | www.wago.com/2009-145/000-006 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue | | |
| Item no.: 2009-145 | | www.wago.com/2009-145 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white | | |
| Item no.: 2009-145/000-002 | | www.wago.com/2009-145/000-002 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow | | |
| Item no.: 2009-145/000-007 | | www.wago.com/2009-145/000-007 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray | | |
| Item no.: 2009-145/000-005 | | www.wago.com/2009-145/000-005 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red | | |
| Item no.: 2009-145/000-012 | | www.wago.com/2009-145/000-012 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange | | |
| Item no.: 2009-145/000-023 | | www.wago.com/2009-145/000-023 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green | | |
| Item no.: 2009-145/000-024 | | www.wago.com/2009-145/000-024 |
| Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet | | |
| Item no.: 248-501/000-006 | | www.wago.com/248-501/000-006 |
| Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue | | |
| Item no.: 248-501/000-007 | | www.wago.com/248-501/000-007 |
| Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray | | |
| Item no.: 248-501/000-002 | | www.wago.com/248-501/000-002 |
| Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow | | |
| Item no.: 248-501/000-012 | | www.wago.com/248-501/000-012 |
| Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange | | |

Subject to changes. Please also observe the further product documentation!



| | |
|-----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------|
| Item no.: 248-501 Mini-WSB marking card; as card; not stretchable; plain; snap-on type; white | www.wago.com/248-501 |
| Item no.: 248-501/000-017 Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green | www.wago.com/248-501/000-017 |
| Item no.: 248-501/000-005 Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red | www.wago.com/248-501/000-005 |
| Item no.: 248-501/000-024 Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet | www.wago.com/248-501/000-024 |
| Item no.: 248-501/000-023 Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green | www.wago.com/248-501/000-023 |
| Item no.: 750-100 Marker card; as a DIN A4 sheet; plain | www.wago.com/750-100 |
| Group marker carrier | |
| Item no.: 750-106 Group marker carrier | www.wago.com/750-106 |
| Supply module | |
| Supply module | |
| Item no.: 750-601 Power Supply; 24 VDC; fuse holder | www.wago.com/750-601 |
| Item no.: 750-610 Power Supply; 24 VDC; fuse holder; Diagnostics | www.wago.com/750-610 |
| Item no.: 750-602 Power Supply; 24 VDC | www.wago.com/750-602 |
| Item no.: 750-612 Power Supply; 0 ... 230 V AC/DC | www.wago.com/750-612 |
| Item no.: 753-612 Power Supply; 0 ... 230 V AC/DC | www.wago.com/753-612 |
| Item no.: 753-602 Power Supply; 24 VDC | www.wago.com/753-602 |
| Pluggable connector | |
| Coding | |
| Item no.: 753-150 753 Series coding elements | www.wago.com/753-150 |

Subject to changes. Please also observe the further product documentation!



Downloads

Documentation

Manual

| | | | |
|---------------------------------------------------------------------------------|-------------------------|---------------|----------|
| System Manual WAGO I/O System 750/753 Decentralized Automation Technology | V 3.3.3 2023 年8月29 日 | pdf 8.7 MB | Download |
| Product Manual 2-channel, 24VDC, 3.0ms high-side switching, with diagnostics | V 1.2.0 | pdf 2.3 MB | Download |
| System Manual Series 750/753 Online HTML | | URL | Download |

Bid Text

| | | | |
|------------------------|--------------|----------------|----------|
| 753-421 X81 - Datei | 2019 年2月19 日 | xml 5.1 kB | Download |
| 753-421 doc - Datei | 2017 年7月13 日 | doc 27.1 kB | Download |

Instruction Leaflet

| | | | |
|----------------------------------------------------------------|--------------|-----------------|----------|
| CCC Ex (Additional information) WAGO-I/O-SYSTEM *750-****/* | 2023 年4月26 日 | pdf 163.6 kB | Download |
|----------------------------------------------------------------|--------------|-----------------|----------|

Additional Information

| | | | |
|-------------------------------------------------------------------------------------|-------------------------|---------------|----------|
| Disposal and Recycling Electrical and electronic equipment, Batteries, Packaging | V 1.1.0 2022 年8月18 日 | pdf 2.2 MB | Download |
|-------------------------------------------------------------------------------------|-------------------------|---------------|----------|

System Description

| | | | |
|---------------------------------------------------------|--|-----------------|----------|
| 750/753 Series I/O-System – General Product Information | | pdf 976.2 kB | Download |
| Overview on WAGO-I/O-SYSTEM 750 approvals | | pdf 223.5 kB | Download |

CAD/CAE-Data

CAD data

| | | | |
|----------------------|--|-----|----------|
| 2D/3D Models 753-421 | | URL | Download |
|----------------------|--|-----|----------|

Subject to changes. Please also observe the further product documentation!



CAE data

| | | |
|---------------------------|---------------------|--------------------------|
| EPLAN Data Portal 753-421 | URL | Download |
| WSCAD Universe 753-421 | URL | Download |
| ZUKEN Portal 753-421 | URL | Download |

Environmental Product Compliance

Compliance Search

| | | |
|------------------------------------------------------------------------------------------------|---------------------|--------------------------|
| Environmental Product Compliance 753-421 2-channel digital input; 24 VDC; 3 ms; Diagnostics | URL | Download |
|------------------------------------------------------------------------------------------------|---------------------|--------------------------|

Installation Notes

Product family

WAGO I/O System 750/753
[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.