



# FCxx\*1)S0G1-0324

e.g. FC25S0G1-0324

\*1) xx No. of contacts 09, 15, 25 or 37

xx	A [mm]	B [mm]	C [mm]
09	30,8	16,4	25
15	39,1	24,7	33,3
25	53	38,5	47,04
37	69,3	54,9	63,5

No.	St.	Part	Type Description/Material	Surface plating/Colour/Class
4	xx	Signal contact	S36 / Brass / AWG 20	0,3µm Au / C-Filter 2nF -45/+85%
3	1	Shell	Steel	tin plated
2	1	Sealing compound	Epoxy resin (-55°C - +85°C)	black
1	1	Insulator	Plastic	black

				Measurement without tolerance occ. to ISO 2768-m SCALE 2:1	TITLE <b>D-Sub Filter-Connector</b>
2	10-12-2009	22216			DWG.NO. FCxxS0G1-0324 REV. 2
1					REPLACEMENT FOR: FCxxS0Gy-0324 b PAGES 1

COMMENT:  
 ALL RIGHTS ARE RESERVED BY US FOR THIS DRAWING. WITHOUT OUR PRIOR CONSENT,  
 IT MAY NEITHER BE DUPLICATED NOR MADE AVAILABLE TO A THIRD PARTY.  
 AND IT ALSO MAY NOT BE IMPROPERLY USED BY THE RECEIVER, OR A THIRD PARTY.