

# RI-70GP Series Dry Reed Switch

7 mm, 1 Form A, 10 Watt



## RI-70GP Series


Ultra-miniature dry-reed switch hermetically sealed in a gas-filled glass envelope. Single-pole, single-throw (SPST) type, having normally open contacts, and containing two magnetically actuated reeds.

The switch is of the double-ended type and may be actuated by an electromagnet, a permanent magnet or a combination of both. The device is intended for use in relays, sensors, pulse counters or similar devices.

## RI-70GP Series Features

- Ideal for ATE switching
- Contact layers: gold, sputtered ruthenium
- Superior glass-to-metal seal and blade alignment
- Excellent life expectancy and reliability
- UL File #E125629

## Dimensions for RI-70GP Series



All Dimension in inches (mm) nominal

## General data for all models RI-70GP

### AT-Customization / Performed Leads

Besides the standard models, customized products can also be supplied offering the following options:

- Operate and release ranges to customer specification
- Cropped and/or performed leads

### Life expectancy and reliability

The life expectancy data given below are valid for a coil energized at 1.25 times the published maximum operate value for each type in the RI-70GP series.

### No load conditions (operating frequency: 100Hz)

Life expectancy: min.  $10^9$  operations with a failure rate of less than  $2 \times 10^{-10}$  with a confidence level of 90%.

End of life criteria:

- Contact resistance >  $1\Omega$  after 2 ms
- Release time > 2 ms (latching or contact sticking).

### Loaded conditions (resistive load: 5 V; 100 mA; operating frequency: 125 Hz)

Life expectancy: min.  $2 \times 10^7$  operations with a failure rate of less than  $10^{-8}$  with a confidence level of 90%.

End of life criteria:

- Contact resistance >  $1\Omega$  after 2.5 ms
- Release time > 1 ms (latching or contact sticking).

### Loaded conditions (resistive load: 20 V; 500 mA; operating frequency: 125 Hz)

Life expectancy: min.  $5 \times 10^6$  operations with a failure rate of less than  $0.5 \times 10^{-7}$  with a confidence level of 90%.

End of life criteria:

- Contact resistance >  $2\Omega$  after 2.5 ms
  - Release time > 2.5 ms (latching or contact sticking).
- Switching different loads involves different life expectancy and reliability data. Further information is available on request.

### Mechanical Data

Contact arrangement is normally open; lead finish is tinned; net mass is approximately 70mg; and can be mounted in any position.

### Shock

The switches are tested in accordance with "IEC 68-2-27", test Ea (peak acceleration 100 G, half sinewave; duration

## Technical Specifications

Parameters	Test Conditions	Units	RI-70GP-XXXX	
<b>Operating Characteristics</b>				
Operate Range		AT*	7-10	10-15
Release Range		AT*	3-9	4-14
Operate Time - including Bounce (typ.)		ms	0.15	0.15
Bounce Time (typ.)		ms	0.035	0.035
Release Time (max)		ms	0.035	0.035
Resonant Frequency (typ.)		Hz	17900	17900
<b>Electrical Characteristics</b>				
Switched Power (max)		W	10	10
Switched Voltage DC (max)		V	170	170
Switched Voltage AC, RMS value (max)		V	120	120
Switched Current DC (max)		mA	500	500
Switched Current AC, RMS value (max)		mA	500	500
Carry Current DC (max)		mA	500	500
Breakdown Voltage (min)		V	210	210
Contact Resistance (initial max.)		mΩ	150	150
Contact Resistance (initial typ.)		mΩ	120	120
Contact Capacitance (max)	without test coil	pF	0.35	0.35
Insulation Resistance (min)	RH ≤ 45%	MΩ	10 <sup>6</sup>	10 <sup>6</sup>

\*AT values are based on full length, measured using Philips Standard Coil (PSC).

11 ms). Such a shock will not cause an open switch (no magnetic field present) to close, nor a switch kept close.

### Vibration

The switches are tested in accordance with "IEC 68-2-26", test Fc (acceleration 10G; below cross-over-frequency 57 to 62 Hz; amplitude 0.75 mm; frequency range 10 to 2000 Hz; duration 90 minutes.) Such a vibration will not cause an open switch ( no magnetic field present) to close, nor a switch kept closed by an 80 AT coil to open.

### Mechanical Strength

The robustness of the terminations is tested in accordance with "IEC 68-2-21", test Ua1 (load 10 N).

### Operating and Storage Temperature

Operating ambient temperature; min: -55°C; max: +125°C. Storage temperature; min: -55°; max: +125°C. Note: Temperature excursions up to 150°C may be permissible. For more information contact your nearest Comus Group sales office.

### Soldering

The switch can withstand soldering heat in accordance with "IEC 68-2-20", test Tb, method 1B: solder bath at 350 ± 10°C for 3.5 ± 0.5 s. Solderability is tested in accordance with "IEC 68-2-20" test Ta, method 3: solder globule temperature 235°C; ageing 1b: 4 hours steam.

### Welding

The leads can be welded.

### Mounting

The leads should not be bent closer than 1 mm to the glass-to-metal seals. Stress on the seals should be avoided Care must be taken to prevent stray magnetic fields from influencing the operating and measuring conditions.

### Ordering Information

#### RI-70GP - XXXX

	<b>AT Ranges</b>
	0710
	1015
<b>Series</b>	

\* As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.