



Product: [5200UP](#)

Audio Cable, 2 Conductor 16 AWG, BC, Unshielded, CM

Product Description

Audio Cable, Rated-CM, 2-16 AWG highly flexible stranded bare copper conductors with PVC insulation, PVC jacket with ripcord

Technical Specifications

Product Overview

| | |
|------------------------|---|
| Suitable Applications: | Security System, Intercom/PA, Audio/Speaker, Power-Limited Controls |
|------------------------|---|

Construction Details

Conductor

| Element | No. of Elements | Size | Stranding | Material |
|--------------|-----------------|--------|-----------|------------------|
| Conductor(s) | 2 | 16 AWG | 65x34 | BC - Bare Copper |

Insulation

| Element | Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|--------------|--------------------------|----------------------|--------------------------|--------------|
| Conductor(s) | PVC - Polyvinyl Chloride | 0.0175 in (0.445 mm) | 0.094 in (2.4 mm) | Black, White |

Outer Jacket

| Material | Nom. Thickness | Nom. Diameter | Ripcord |
|--------------------------|--------------------|--------------------|---------|
| PVC - Polyvinyl Chloride | 0.015 in (0.38 mm) | 0.218 in (5.54 mm) | Yes |

| | |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.218 in (5.54 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

Electricals

| Element | Nom. Conductor DCR | Nom. Capacitance Cond-to-Cond | Max. Current |
|--------------|--------------------|-------------------------------|--------------------------------|
| Conductor(s) | 4.05 Ohm/1000ft | 30 pF/ft (98 pF/m) | 15.7 Amps per conductor @ 25°C |

Voltage

| UL Voltage Rating |
|-------------------|
| 300 V (CM) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating |
|----------------|----------------|
| 75°C | -20°C to +75°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 2.2 in (56 mm) | 2.2 in (56 mm) |

| | |
|--------------------|----------------|
| Max. Pull Tension: | 65 lbs (29 kg) |
| Bulk Cable Weight: | 26 lbs/1000ft |

Standards and Compliance

| | |
|----------------------------------|--|
| Environmental Suitability: | Indoor (Not Riser or Plenum), Indoor |
| Flammability / Reaction to Fire: | UL 1685 UL loading , IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 800, CM |
| European Directive Compliance: | EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE) |
| UK Regulation Compliance: | UKCA Mark |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.497 Revision Date: 04-28-2023 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC | Footnote |
|-----------------|-------------|--------------|----------|--------------|----------|
| 5200UP 010500 | Black | Reel | 500 ft | 612825157670 | C |
| 5200UP 010U500 | Black | UnReel | 500 ft | 612825421436 | |
| 5200UP 0101000 | Black | Reel | 1,000 ft | 612825157694 | |
| 5200UP 010U1000 | Black | UnReel | 1,000 ft | 612825157687 | |
| 5200UP 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825157571 | |
| 5200UP D15500 | Blue | Reel | 500 ft | 612825157557 | C |
| 5200UP D15U500 | Blue | UnReel | 500 ft | 612825421405 | |
| 5200UP D151000 | Blue | Reel | 1,000 ft | 612825157588 | |
| 5200UP D15U1000 | Blue | UnReel | 1,000 ft | 612825157564 | |
| 5200UP D15Z1000 | Blue | ReelTuff Box | 1,000 ft | 612825157755 | |
| 5200UP 008U500 | Gray | UnReel | 500 ft | 612825421412 | |
| 5200UP 0081000 | Gray | Reel | 1,000 ft | 612825157618 | C |
| 5200UP 008U1000 | Gray | UnReel | 1,000 ft | 612825157625 | |
| 5200UP 008Z1000 | Gray | ReelTuff Box | 1,000 ft | 612825157663 | |
| 5200UP 005500 | Green, Dark | Reel | 500 ft | 612825359074 | |
| 5200UP 005U500 | Green, Dark | UnReel | 500 ft | 612825157632 | |
| 5200UP 0051000 | Green, Dark | Reel | 1,000 ft | 612825157601 | |
| 5200UP 009U500 | White | UnReel | 500 ft | 612825421429 | |
| 5200UP 0091000 | White | Reel | 1,000 ft | 612825157649 | C |
| 5200UP 009U1000 | White | UnReel | 1,000 ft | 612825157656 | |
| 5200UP 009Z1000 | White | ReelTuff Box | 1,000 ft | 612825336549 | |

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.