72 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 172129 N-Type Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle Connector			A		Cable	Cable Con		
135" 180° 225" 270° 270° D-Fint Bulkhead	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132245 SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Right Angle		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 72 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	172129 N-Type BHD JK RG N-Type Jack Straight Crimp Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel None Beryllium Copper Gold 11 GHz N-Type Jack Straigh 0°	unt
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY			AND MUST NOT BE U TAL TO CUSTOM CAI CED OR TRANSCRIBI /RITTEN CONSENT O .NCE OF THIS DRAWI	T BE USED SCRIBED ENT OF Part No: SAMA-RA-JK/N-ST-JK G174 72I			UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	