

## FO connectors - FOC-V14-C1ZNI-T/SJFG - 1408030

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Push-pull connector (version 14), die-cast zinc, with SC-RJ insert for GOF, for cable diameter of 5.5 mm ... 10 mm, cable outlet at the top

### Product Features

- Push-pull ADVANCE connector
- Locking system to prevent inadvertent removal
- Highest ESD and EMC resistance for reliable transmission



### Key Commercial Data

Packing unit	1 pc
Custom tariff number	85367000
Country of origin	Germany

### Technical data

#### Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Insertion/withdrawal cycles	≥ 50
External cable diameter	5.5 mm ... 10 mm
Cable exit	angled

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (assembly)	-10 °C ... 40 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Degree of protection	IP67

#### Material data

Housing material	Zinc die-cast
------------------	---------------

# FO connectors - FOC-V14-C1ZNI-T/SJFG - 1408030

## Technical data

### Standards and Regulations

Standards/regulations	IEC PAS 61076-3-117
-----------------------	---------------------

## Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27061803
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	19170122

### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002641
ETIM 5.0	EC001122

### UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

## Drawings

Dimensional drawing



