

**Data sheet | Item number: 790-124**

Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ...  
24 mm



[www.wago.com/790-124](http://www.wago.com/790-124)



**Data  
Notes**

Safety information

Cannot be used for connecting ground conductors!

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Technical data

Main product function	Shield clamping saddles
Safety information	Cannot be used for connecting ground conductors!

## Physical data

Width	27 mm / 1.063 inches
-------	----------------------

## Material Data

Color	silver-colored
Weight	21 g
Material	Steel V2A Stainless steel

## Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-14-11-50
eCl@ss 9.0	27-14-11-50
ETIM 8.0	EC002020
ETIM 7.0	EC002020
PU (SPU)	50 (10) pcs
Packaging type	box
Country of origin	DE
GTIN	4017332356961
Customs tariff number	85369010000

## Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

## Optional accessories

### Mounting

Shield termination		
<b>Item no.: 790-101</b>		
Isolated mounting carrier; for busbar with sheet metal screw (3.5 x 9) mm; gray		<a href="http://www.wago.com/790-101">www.wago.com/790-101</a>
<b>Item no.: 790-100</b>		
Isolated mounting carrier; for busbar with screw M4 x 8 mm; gray		<a href="http://www.wago.com/790-100">www.wago.com/790-100</a>

### N-busbar

Subject to changes. Please also observe the further product documentation!



## Shield termination

<b>Item no.: 790-191</b> U-shaped busbar; Cu 10 mm x 3 mm; for 8 I/O; suitable for 750 Series I/O modules; silver-colored	<a href="http://www.wago.com/790-191">www.wago.com/790-191</a>
<b>Item no.: 790-190</b> U-shaped busbar; Cu 10 mm x 3 mm; for 5 I/O; suitable for 750 Series I/O modules; silver-colored	<a href="http://www.wago.com/790-190">www.wago.com/790-190</a>
<b>Item no.: 790-192</b> U-shaped busbar; Cu 10 mm x 3 mm; for 5 I/O; suitable for 750 Series I/O modules; silver-colored	<a href="http://www.wago.com/790-192">www.wago.com/790-192</a>
<b>Item no.: 790-193</b> U-shaped busbar; Cu 10 mm x 3 mm; for 8 I/O; suitable for 750 Series I/O modules; silver-colored	<a href="http://www.wago.com/790-193">www.wago.com/790-193</a>

## Mounting accessories

<b>Item no.: 210-133</b> Busbar; tin-plated; 1000 mm long; Cu 10 mm x 3 mm; white	<a href="http://www.wago.com/210-133">www.wago.com/210-133</a>
<b>Item no.: 790-133</b> Busbar; tin-plated; 30 mm long; Cu 10 mm x 3 mm; silver-colored	<a href="http://www.wago.com/790-133">www.wago.com/790-133</a>
<b>Item no.: 790-134</b> Busbar; tin-plated; 50 mm long; Cu 10 mm x 3 mm; silver-colored	<a href="http://www.wago.com/790-134">www.wago.com/790-134</a>

## Carrier rail

## Shield termination

<b>Item no.: 790-145</b> Carrier rail; with special perforations; 1000 mm long; tin-plated; silver-colored	<a href="http://www.wago.com/790-145">www.wago.com/790-145</a>
---	--

## Shield termination

## Shield termination

<b>Item no.: 790-115</b> Carrier with 2 grounding feet; parallel to carrier rail; 125 mm long; Cu 10 mm x 3 mm; gray	<a href="http://www.wago.com/790-115">www.wago.com/790-115</a>
<b>Item no.: 790-113</b> Carrier with grounding foot; 90° to carrier rail; 45 mm long; Cu 10 mm x 3 mm; suitable for 790 Series shield clamping saddles; gray	<a href="http://www.wago.com/790-113">www.wago.com/790-113</a>
<b>Item no.: 790-114</b> Carrier with grounding foot; parallel to carrier rail; 45 mm long; Cu 10 mm x 3 mm; suitable for 790 Series shield clamping saddles and 791 Series shield clamps; gray	<a href="http://www.wago.com/790-114">www.wago.com/790-114</a>

## Downloads

## Documentation

## Bid Text

790-124 X81 - Datei	2019 年2月19 日	xml 2.8 kB	Download
790-124	2018 年11月28 日	doc 24.1 kB	Download

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

doc - Datei

---

## CAD/CAE-Data

### CAE data

WSCAD Universe 790-124	<a href="#">URL</a>	<a href="#">Download</a>
ZUKEN Portal 790-124	<a href="#">URL</a>	<a href="#">Download</a>
EPLAN Data Portal 790-124	<a href="#">URL</a>	<a href="#">Download</a>

### CAD data

2D/3D Models 790-124	<a href="#">URL</a>	<a href="#">Download</a>
----------------------	---------------------	--------------------------

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 790-124 Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm	<a href="#">URL</a>	<a href="#">Download</a>
---	---------------------	--------------------------

## Installation Notes



WAGO's shield connection system is highly effective because the clamping unit can be brought very close to the unshielded part of the cable.

Additionally, the spring material is part of the clamping saddle, providing a good electrical connection (the system also acts as a partial strain relief). The spring element integrated in the shield clamping saddle compensates for deformation and settling that results from a connected shield.

---

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



### Installation

The shield clamping saddle is shipped ready for direct connection to the (10 x 3) mm busbar or to a drilled mounting plate. After connection, tighten the knurled screw to complete the installation.

Maximum tightening torque: 0.5 Nm



### Removal

To remove the clamping saddle, unscrew until ratcheted mechanism is released, then slightly tip saddle and remove the clamping saddle.



Carrier with grounding foot\* (790-113), 45 mm long, busbar 90° to the DIN-rail

\*for all shield clamping saddle sizes



Carrier with grounding foot\* (790-114), 45 mm long, busbar parallel to the DIN-rail

\*for all shield clamping saddle sizes

Subject to changes. Please also observe the further product documentation!



Carrier with grounding foot\* (790-1145), 125 mm long, busbar parallel to the rail



Securing an additional shield clamping saddle.

\*for all shield clamping saddle sizes




Tightening/removing a shield clamping saddle.



After connection, tighten the knurled screw to complete the installation.

Recommended tightening torque: 0.5 Nm



To remove the clamping saddle, unscrew until ratcheted mechanism is released, then slightly tip saddle and remove the clamping saddle.

---

Subject to changes. Please also observe the further product documentation!



Carrier with grounding foot – busbar parallel to the rail



Insulated mounting carriers for a common shield reference potential, independent of housing potential



U-shaped (10 x 3) mm copper busbar



Snap shield clamping saddles into any metal plate (max. thickness: 3 mm).

Subject to changes. Please also observe the further product documentation!