

1.0 SCOPE

- 1.1 **Scope.** This specification covers the detail requirements for a low voltage, micropower dual operational amplifier.

It is highly recommended that this datasheet be used as a baseline for new military or aerospace specification control drawings.

- 1.2 **Part Number.** The complete part numbers per Table 1 of this specification follow:

<u>Device</u>	<u>Part Number</u>	<u>Package</u>
A	OP-290AZ/883	Z
A	OP-290ARC/883	RC

- 1.2.3 **Case Outline.** The case outline is designated as follows:

<u>Letter</u>	<u>Case Outline</u> (Lead Finish per MIL-M-38510)
Z	8-lead ceramic dual-in-line package (CERDIP)
RC	20-contact hermetic leadless chip carrier (LCC)

- 1.3 **Absolute Maximum Ratings.** ($T_A = +25^\circ\text{C}$, unless otherwise noted)

Supply Voltage.....	$\pm 18\text{V}$
Input Voltage.....	[$(V-) - 20\text{V}$] to [$(V+) + 20\text{V}$]
Differential Input Voltage.....	[$(V-) - 20\text{V}$] to [$(V+) + 20\text{V}$]
Output Short-Circuit Duration.....	Continuous
Storage Temperature Range.....	-65°C to +150°C
Lead Temperature Range (Soldering, 60 sec).....	300°C
Maximum Junction Temperature (T_J).....	-65°C to 150°C
Operating Temperature Range.....	-55°C to +125°C

1.5 Thermal Characteristics:

Thermal Resistance, CERDIP (Z) package:

$$\text{Junction-to-Case } (\Theta_{JC}) = 26^\circ\text{C/W MAX}$$

$$\text{Junction-to-Ambient } (\Theta_{JA}) = 119^\circ\text{C/W MAX}$$

Thermal Resistance, leadless chip carrier (RC) package:

$$\text{Junction-to-Case } (\Theta_{JC}) = 30^\circ\text{C/W MAX}$$

$$\text{Junction-to-Ambient } (\Theta_{JA}) = 120^\circ\text{C/W MAX}$$

OP-290

TABLE 1

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; $T_A = +25^\circ C$; unless otherwise specified.

Characteristics	Symbol	Special Conditions	<u>OP-290/883</u> <u>LIMITS A</u>		Units
			MIN	MAX	
Input Offset Voltage	V_{OS}	$-55^\circ C \leq T_A \leq +125^\circ C$	--	200	μV
			--	500	μV
Input Offset Current	I_{OS}	$V_{CM} = 0V$	--	3	nA
		$V_{CM} = 0V, -55^\circ C \leq T_A \leq +125^\circ C$	--	5	
Input Bias Current	I_B	$V_{CM} = 0V$	--	± 15	nA
		$V_{CM} = 0V, -55^\circ C \leq T_A \leq +125^\circ C$	--	± 20	
Large-Signal Voltage Gain	A_{VO}	$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 100k\Omega$	700	--	V/mV
		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 100k\Omega,$ $-55^\circ C \leq T_A \leq +125^\circ C$	225	--	V/mV
		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 10k\Omega$	350	--	V/mV
		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 10k\Omega,$ $-55^\circ C \leq T_A \leq +125^\circ C$	125	--	V/mV
		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 2k\Omega$	125	--	V/mV
		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 2k\Omega,$ $-55^\circ C \leq T_A \leq +125^\circ C$	50	--	V/mV

TABLE 1 (Continued)

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; $T_A = +25^\circ C$; unless otherwise specified.

Characteristics	Symbol	Special Conditions	MIN	MAX	Units
		$V_+ = +5V, V_- = 0V,$ $1V \leq V_O \leq 4V; R_L = 100k\Omega$	200	--	V/mV
Large-Signal Voltage Gain (Cont'd)	A_{VO}	$V_+ = +5V, V_- = 0V,$ $1V \leq V_O \leq 4V; R_L = 100k\Omega$ $-55^\circ C \leq T_A \leq +125^\circ C$	100	--	V/mV
		$V_+ = +5V, V_- = 0V,$ $1V \leq V_O \leq 4V; R_L = 10k\Omega$	100	--	V/mV
		$V_+ = +5V, V_- = 0V,$ $1V \leq V_O \leq 4V; R_L = 10k\Omega$ $-55^\circ C \leq T_A \leq +125^\circ C$	50	--	V/mV
Output Voltage Swing	V_O	$V_S = \pm 15V, R_L = 10k\Omega$	± 13.5	--	V
		$V_S = \pm 15V, R_L = 10k\Omega,$ $-55^\circ C \leq T_A \leq +125^\circ C$	± 13	--	V
		$V_S = \pm 15V, R_L = 2k\Omega$	± 10.5	--	V
		$V_S = \pm 15V, R_L = 2k\Omega,$ $-55^\circ C \leq T_A \leq +125^\circ C$	± 10	--	V
Output Voltage Swing	V_{OH}	$V_+ = +5V, V_- = 0V, R_L = 2k\Omega$	4.0	--	V
		$V_+ = +5V, V_- = 0V, R_L = 2k\Omega,$ $-55^\circ C \leq T_A \leq +125^\circ C$	3.9	--	V

OP-290

TABLE 1 (Continued)

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; $T_A = +25^\circ C$; unless otherwise specified.

Characteristic	Symbol	Special Conditions	OP-290/883 <u>LIMITS A</u>		Units
Output Voltage Swing	V_{OL}	$V_+ = +5V$, $V_- = 0V$, $R_L = 10k\Omega$	--	50	μV
		$V_+ = +5V$, $V_- = 0V$, $R_L = 10k\Omega$, $-55^\circ C \leq T_A \leq +125^\circ C$	--	100	μV
Common-Mode Rejection	CMR	$V_+ = +5V$, $V_- = 0V$, $0V \leq V_{CM} \leq 4V$	90	--	dB
		$V_+ = +5V$, $V_- = 0V$, $0V \leq V_{CM} \leq 3.5V$, $-55^\circ C \leq T_A \leq +125^\circ C$	80	--	dB
Power-Supply Rejection Ratio	PSRR	$V_S = \pm 15V$, $-15V \leq V_{CM} \leq 13.5V$	100	--	dB
		$V_S = \pm 15V$, $-15V \leq V_{CM} \leq 13.5V$, $-55^\circ C \leq T_A \leq +125^\circ C$	90	--	dB
Supply Current (Note 2)	I_{SY}	No Load, $V_S = \pm 1.5V$	--	5.6	$\mu V/V$
		No Load, $V_S = \pm 1.5V$, $-55^\circ C \leq T_A \leq +125^\circ C$	--	10	$\mu V/V$
		No Load, $V_S = \pm 15V$	--	40	μA
		No Load, $V_S = \pm 15V$, $-55^\circ C \leq T_A \leq +125^\circ C$	--	60	μA

TABLE 1 (Continued)

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; $T_A = +25^\circ C$; unless otherwise specified.

Characteristic	Symbol	Special Conditions	MIN	MAX	Units
Slew Rate	SR	$V_S = \pm 15V$	5	--	V/ms
Input Offset Voltage	TCV_{OS}	$V_S = \pm 15V$	--	3	$\mu V/^\circ C$
Temperature Coefficient					

Note 1. IVR guaranteed by CMR test.

Note 2. I_{SY} limit = total of both amplifiers.

TABLE 2

OP-290/883

12

**Electrical Test Requirements
For Class B Devices**

MIL-STD-883 Test Requirement	Subgroups (see Table 3)
Interim Electrical Parameters (pre Burn-In)	1
Final Electrical Test Parameters	1*, 2, 3, 4, 5, 6
Group A Test Requirements	1, 2, 3, 4, 5, 6, 7, 8

* PDA applies to Subgroup 1 only.

No other Subgroups are included in PDA.

OP-290

TABLE 3
Group A Inspection

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; unless otherwise specified.

Characteristic	Symbol	Special Conditions	OP-290/883 <u>LIMITS A</u>		
			MIN	MAX	Units
Subgroup 1. $T_A = +25^\circ C$	V_{OS}		--	200	μV
	I_{OS}	$V_{CM} = 0V$	--	3	nA
	I_B	$V_{CM} = 0V$	--	± 15	nA
	CMR (Note 1)	$V_+ = +5V, V_- = 0V, V_{CM} = 0V, 4V$ $V_S = \pm 15V, V_{CM} = -15V, 13.5V$	90 100	-- --	dB dB
	PSRR	$V_S = \pm 1.5V, \pm 15V$	--	5.6	$\mu V/V$
	I_{SY} (Note 2)	$V_S = \pm 1.5V, \text{No Load}$ $V_S = \pm 15V, \text{No Load}$	-- --	30 40	μA μA
Subgroup 2. $T_A = +125^\circ C$	V_{OS}		--	500	μV
	I_{OS}	$V_{CM} = 0V$	--	5	nA
	I_B	$V_{CM} = 0V$	--	± 20	nA
	CMR (Note 1)	$V_+ = +5V, V_- = 0V, V_{CM} = 0V, 3.5V$ $V_S = \pm 15V, V_{CM} = -15V, 13.5V$	80 90	-- --	dB dB

TABLE 3
Group A Inspection

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; unless otherwise specified.

Characteristic	Symbol	Special Conditions	MIN	MAX	Units
Subgroup 2. $T_A = +125^\circ C$	PSRR	$V_S = \pm 1.5V, \pm 15V$	--	10	$\mu V/V$
(Cont'd)	I_{SY} (Note 2)	$V_S = \pm 1.5V$, No Load $V_S = \pm 15V$, No Load	--	50	μA
			--	60	μA
Subgroup 3. $T_A = -55^\circ C$		All Tests, Limits, and Conditions are the same as for Subgroup 2.			
Subgroup 4. $T_A = +25^\circ C$		$V_S = \pm 15V, V_O = \pm 10V$, $R_L = 100k\Omega$	700	--	V/mV
		$V_S = \pm 15V, V_O = \pm 10V$, $R_L = 10k\Omega$	350	--	V/mV
A_{VO}		$V_S = \pm 15V, V_O = \pm 10V$, $R_L = 2k\Omega$	125	--	V/mV
		$V+ = +5V, V- = 0V$, $V_O = 1V, 4V; R_L = 100k\Omega$	200	--	V/mV
		$V+ = +5V, V- = 0V$, $V_O = 1V, 4V; R_L = 10k\Omega$	100	--	V/mV
V_O		$V_S = \pm 15V, R_L = 10k\Omega$	± 13.5	--	V
		$V_S = \pm 15V, R_L = 2k\Omega$	± 10.5	--	V
V_{OH}		$V+ = +5V, V- = 0V$ $R_L = 2k\Omega$	4.0	--	V
V_{OL}		$V+ = +5V, V- = 0V$ $R_L = 10k\Omega$	--	50	μV

TABLE 3
Group A Inspection

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; unless otherwise specified.

Characteristic	Symbol	Special Conditions	OP-290/883 LIMITS A		Units
			MIN	MAX	
Subgroup 5. $T_A = +125^\circ C$		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 100k\Omega$	225	--	V/mV
		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 10k\Omega$	125	--	V/mV
A_{VO}		$V_S = \pm 15V, V_O = \pm 10V,$ $R_L = 2k\Omega$	50	--	V/mV
		$V+ = +5V, V- = 0V,$ $V_O = 1V, 4V; R_L = 100k\Omega$	100	--	V/mV
		$V+ = +5V, V- = 0V,$ $V_O = 1V, 4V; R_L = 10k\Omega$	50	--	V/mV
V_O		$V_S = \pm 15V, R_L = 10k\Omega$	± 13	--	V
		$V_S = \pm 15V, R_L = 2k\Omega$	± 10	--	V
V_{OH}		$V+ = +5V, V- = 0V,$ $R_L = 2k\Omega$	3.9	--	V
V_{OL}		$V+ = +5V, V- = 0V,$ $R_L = 10k\Omega$	--	100	μV
Subgroup 6. $T_A = -55^\circ C$		All Tests, Limits, and Conditions are the same as for Subgroup 5.			

TABLE 3
Group A Inspection

$V_S = \pm 1.5V$ and $\pm 15V$; $R_S = 50\Omega$; unless otherwise specified.

Characteristic	Symbol	Special Conditions	MIN	MAX	Units
Subgroup 7.	SR	$V_S = \pm 15V$ $T_A = +25^\circ C$	5	--	V/ms
Subgroup 8.	TCV_{OS}	$V_S = \pm 15V$ $T_A = -55^\circ C, +125^\circ C$	--	3	$\mu V/C$

Note 1. IVR guaranteed by CMR test.

Note 2. I_Y limit = total of both amplifiers.

3.2.1 Simplified Schematic and Pin Connections

