

Specification Sheet

Part Number: TAG5-100

Dot matrix printable self-laminating vinyl has a smooth surface, allowing for the highest resolution and print contrast using an impact printer. The material is a conformable vinyl, allowing it to wrap and stay around wires and cable.

The acrylic-based adhesive bonds to a wide variety of substrates and will remain in place long term.

Tabtag dot matrix labels are specifically made for use in dot matrix printers for fast and easy printing.

Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.



Dot Matrix Label, Self-Laminating, 0.80" x .50" x 1.437", 6 Across, White, 5000/pkg

Article Number 595-05100

Type TAG5

Color White (WH)

Quantity Per pack

Product Description HellermannTyton's self-laminating labels are used for marking wires and cable. The clear tail overlaps and protects the printed information from abrasion, chemicals and solvents and resists UV exposure. When printed using any standard dot matrix printer, clear marking and high high-contrast imaging against the wire make this the perfect choice for durable identification.

| | |
|---------------------------------|---|
| Short Description | Dot Matrix Label, Self-Laminating, 0.80" x .50" x 1.437", 6 Across, White, 5000/pkg |
| Global Part Name | TAG5-100-WH |
| Local Order Number 2 | 595-05100 |
| Fixation Method | Pasting / Stick |
| Variant | Adhesive label |
| Width W (Imperial) | 0.8 |
| Width W (Metric) | 20.3 |
| Bundle Diameter Min (Imperial) | 0.15 |
| Bundle Diameter Min (Metric) | 3.80 |
| Bundle Diameter Max (Imperial) | 0.29 |
| Bundle Diameter Max (Metric) | 7.60 |
| Thickness T (Metric) | 75.0 |
| Width of Liner (Metric) | 160.00 |
| Width of Liner (Imperial) | 6.3 |
| Outside Diameter Max (Imperial) | 0.299 |
| Outside Diameter Min (Metric) | 3.8 |

| | |
|---------------------------------|---|
| Outside Diameter Min (Imperial) | 0.149 |
| Outside Diameter Max (Metric) | 7.60 |
| Material | Type 100, Vinyl, white, self-laminating (100) |
| Material Shortcut | 100 |
| Adhesive | Acrylic |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Adhesive Operating Temperature | -51°F to +200°F (-46°C to +93°C) |
| Operating Temperature | -51°F to +200°F (-46°C to +93°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL-Recognized |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 5000 |
| Package Quantity (Metric) | 5000 |

Customs Number 3919905060

Labels per Column 6

Labels per Row 6

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)