



POLE	MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGHT IN/MM
3	1200280735	483031P03M006	1.97' +1.75" -0 [0.6M +44.5 -0]
3	1200875021	483031P03M010	3.28' +2.19" -0 [1.0M +55.6 -0]
3	1200878003	483031P03M020	6.56' +3.50" -0 [2.0M +88.9 -0]
4	1200280773	484031P03M006	1.97' +1.75" -0 [0.6M +44.5 -0]
4	1200875027	484031P03M010	3.28' +2.19" -0 [1.0M +55.6 -0]

CONNECTOR SPECIFICATION:	
VOLTAGE RATING	3-4POL:60V/AC 75V/DC
AMPERAGE RATING	3 AMPS
PROTECTION	IP68
OPERATING TEMPERATURE	-30°C TO +80°C
UL CERTIFICATIONS	UL listed, File #E152210
CSA CERTIFICATIONS	CSA CERTIFIED, File LR6837

ITEM	COMPONENT	MATERIAL	FINISH
1	INSERT	POLYURETHANE (PUR)	BLACK
2	CONTACT SOCKET	COPPER ALLOY	GOLD OVER NICKEL
3	COUPLING NUT	BRASS	NICKEL PLATED
4	OVERMOLD	TPU	YELLOW
5	O-RING (FEMALE)	VITON	RED
6	CABLE 0.25mm ² /24AWG, (COPPER STRANDING) 3/4 CONDUCT. 300V	JACKET: PUR/PVC	BLACK

DESCRIPTION EC NO: WEU2010-0328 DRWN: REISSNER 2010/02/04 CHKD: FP APPR: NSTAUDIG 2010/02/11	QUALITY SYMBOLS ▽ = 0 ▽/C = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE 2:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
		mm	INCH	DRAWN BY REISSNER	DATE 2010/02/04	NC/MIC 3/4P F/MM 90/ST AWG 24 PUR/PVC			
		4 PLACES ±---	±---	CHECKED BY FP	DATE 2010/02/04				
		3 PLACES ±---	±---	APPROVED BY NSTAUDIG		DATE 2010/02/10	MOLEX INCORPORATED SD-120087-032		
2 PLACES ±---	±.01	MATERIAL NO.		DOCUMENT NO.	SHEET NO.				
1 PLACE ±0.3	±---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
1 REV									