

https://www.phoenixcontact.com/us/products/1002665



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Comfort device adapter with CrossLink® interface and moveable DIN rail, rated current: 25 A

Your advantages

- · Cable ends ultrasound-compressed
- · Snap-on mechanism for quick and easy attachment to the CrossPowerSystem power distribution board

Commercial data

Item number	1002665
Packing unit	1 pc
Minimum order quantity	4 pc
Sales key	C470
Product key	CK7852
Catalog page	Page 53 (C-5-2019)
GTIN	4055626468143
Weight per piece (including packing)	131 g
Weight per piece (excluding packing)	127 g
Customs tariff number	85369095
Country of origin	DE



https://www.phoenixcontact.com/us/products/1002665



Technical data

Product properties

Product type	Adapter
Product family	CrossPowerSystem
Application	Device adapter

Electrical properties

Rated voltage	690 V AC (IEC)
	600 V AC (UL)
Rated current	25 A (IEC)
	20 A (UL)
Rated surge voltage	6 kV

Dimensions

Width	45 mm
Height	160 mm
Depth	45 mm



1002665

https://www.phoenixcontact.com/us/products/1002665

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1002665



EAC

Approval ID: RU C-DE.BL08.B.00511



UL Listed

Approval ID: FILE E 123528



cUL Listed

Approval ID: FILE E 123528

cULus Listed



https://www.phoenixcontact.com/us/products/1002665



Classifications

UNSPSC 21.0

ECLASS

ECLASS	-11.0	27371392
ECLASS	:-13.0	27371392
ECLASS	:-12.0	27371392
ETIM		
ETIM 8.0)	EC002498
UNSPSC		

39121100



https://www.phoenixcontact.com/us/products/1002665



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values



https://www.phoenixcontact.com/us/products/1002665



Mandatory accessories

EM-CPS-225 - Power distribution board

1002634

https://www.phoenixcontact.com/us/products/1002634



Modular power distribution board with CrossLink® interface, 125 A, 3-pos., touch-proof and protection against polarity reversal, width: 225 mm

EM-CPS-405 - Power distribution board

1002635

https://www.phoenixcontact.com/us/products/1002635



Modular power distribution board with CrossLink® interface, 125 A, 3-pos., touch-proof and protection against polarity reversal, width: 405 mm

Accessories



https://www.phoenixcontact.com/us/products/1002665



EM-CPS-DAE-45 - Adapter

1003293

https://www.phoenixcontact.com/us/products/1003293



Height extension for Comfort device adapter, width: 45 mm

EM-CPS-DAES-45 - Adapter

1003294

https://www.phoenixcontact.com/us/products/1003294



Lateral extension of the height extension for Comfort device adapter, width: 45 mm



https://www.phoenixcontact.com/us/products/1002665



EM-CPS-TS-45 - Adapter

1003295

https://www.phoenixcontact.com/us/products/1003295



Comfort DIN rail, additional DIN rail for Comfort device adapter

EM-CPS-DHS-45 - Adapter

1003296

https://www.phoenixcontact.com/us/products/1003296



Siemens device mount, positioning element for Siemens S0 and S00 switching devices



https://www.phoenixcontact.com/us/products/1002665



EM-CPS-DHE-45 - Adapter

1002663

https://www.phoenixcontact.com/us/products/1002663



Eaton device mount, positioning element for Eaton PKZ switching devices

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com