

# Central<sup>TM</sup> Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA  
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

BSS50  
BSS51  
BSS52

NPN SILICON  
DARLINGTON TRANSISTORS

JEDEC TO-39 CASE

## DESCRIPTION

The CENTRAL SEMICONDUCTOR BSS50 series types are NPN Silicon Darlington Transistors designed for industrial switching applications.

## MAXIMUM RATINGS (T<sub>A</sub>=25°C)


	SYMBOL	BSS50	BSS51	BSS52	UNITS
Collector-Base Voltage	V <sub>CB0</sub>	60	80	90	V
Collector-Emitter Voltage	V <sub>CER</sub>	45	60	80	V
Emitter-Base Voltage	V <sub>EBO</sub>		5.0		V
Collector Current	I <sub>C</sub>		1.0		A
Collector Current (Peak)	I <sub>CM</sub>		2.0		A
Base Current (Peak)	I <sub>BM</sub>		100		mA
Power Dissipation	P <sub>D</sub>		0.8		W
Power Dissipation (T <sub>C</sub> =25°C)	P <sub>D</sub>		5.0		W
Operating and Storage					
Junction Temperature	T <sub>J</sub> , T <sub>stg</sub>		-65 to +200		°C
Thermal Resistance	θ <sub>JA</sub>		219		°C/W
Thermal Resistance	θ <sub>JC</sub>		35		°C/W

## ELECTRICAL CHARACTERISTICS (T<sub>A</sub>=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	BSS50		BSS51		BSS52		UNITS
		MIN	MAX	MIN	MAX	MIN	MAX	
I <sub>CB0</sub>	V <sub>CB</sub> =Rated V <sub>CER</sub>		50		50		50	nA
I <sub>EBO</sub>	V <sub>EB</sub> =4.0V		50		50		50	nA
V <sub>CE(SAT)</sub>	I <sub>C</sub> =500mA, I <sub>B</sub> =500μA		1.3		1.3		1.3	V
V <sub>CE(SAT)</sub>	I <sub>C</sub> =500mA, I <sub>B</sub> =500μA, T <sub>A</sub> =200°C		1.3		1.3		1.3	V
V <sub>CE(SAT)</sub>	I <sub>C</sub> =1.0A, I <sub>B</sub> =1.0mA		-		1.6		-	V
V <sub>CE(SAT)</sub>	I <sub>C</sub> =1.0A, I <sub>B</sub> =1.0mA, T <sub>A</sub> =200°C		-		2.3		-	V
V <sub>CE(SAT)</sub>	I <sub>C</sub> =1.0A, I <sub>B</sub> =4.0mA		1.6		-		1.6	V
V <sub>CE(SAT)</sub>	I <sub>C</sub> =1.0A, I <sub>B</sub> =4.0mA, T <sub>A</sub> =200°C		1.6		-		1.6	V
V <sub>BE(SAT)</sub>	I <sub>C</sub> =500mA, I <sub>B</sub> =500μA		1.9		1.9		1.9	V
V <sub>BE(SAT)</sub>	I <sub>C</sub> =1.0A, I <sub>B</sub> =1.0mA		-		2.2		-	V
V <sub>BE(SAT)</sub>	I <sub>C</sub> =1.0A, I <sub>B</sub> =4.0mA		2.2		-		2.2	V
V <sub>BE(ON)</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> =150mA	1.3	1.65	1.3	1.65	1.3	1.65	V
V <sub>BE(ON)</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> =500mA	1.4	1.75	1.4	1.75	1.4	1.75	V
h <sub>FE</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> =150mA		1K		1K		1K	
h <sub>FE</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> =500mA		2K		2K		2K	
h <sub>fe</sub>	V <sub>CE</sub> =5.0V, I <sub>C</sub> =500mA, f=35MHz		10 TYP		10 TYP		10 TYP	
t <sub>on</sub>	I <sub>C</sub> =500mA, I <sub>B1</sub> =I <sub>B2</sub> =0.5mA		0.4 TYP		0.4 TYP		0.4 TYP	μs
t <sub>off</sub>	I <sub>C</sub> =500mA, I <sub>B1</sub> =I <sub>B2</sub> =0.5mA		1.5 TYP		1.5 TYP		1.5 TYP	μs
t <sub>on</sub>	I <sub>C</sub> =1.0A, I <sub>B1</sub> =I <sub>B2</sub> =1.0mA		0.4 TYP		0.4 TYP		0.4 TYP	μs
t <sub>off</sub>	I <sub>C</sub> =1.0A, I <sub>B1</sub> =I <sub>B2</sub> =1.0mA		1.5 TYP		1.5 TYP		1.5 TYP	μs

(See Reverse Side)

# JEDEC TO-39 CASE - MECHANICAL OUTLINE



All Dimensions in Inches (mm).

Lead Code:

1. Emitter
2. Base
3. Collector

**Central**<sup>TM</sup>  
**Semiconductor Corp.**

## OUTSTANDING SUPPORT AND SUPERIOR SERVICES



---

### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

---

### DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

---

### REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

---

### CONTACT US

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.  
145 Adams Avenue  
Hauppauge, NY 11788 USA  
Main Tel: (631) 435-1110  
Main Fax: (631) 435-1824  
Support Team Fax: (631) 435-3388  
[www.centrasemi.com](http://www.centrasemi.com)

**Worldwide Field Representatives:**  
[www.centrasemi.com/wwreps](http://www.centrasemi.com/wwreps)

**Worldwide Distributors:**  
[www.centrasemi.com/wwdistributors](http://www.centrasemi.com/wwdistributors)

---

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: [www.centrasemi.com/terms](http://www.centrasemi.com/terms)



<http://www.centrasemi.com>

# Product End of Life Notification

<b>PDN ID:</b>	PDN01210
<b>Notification Date:</b>	2/18/22
<b>Last Buy Date:</b>	8/18/22
<b>Last Shipment Date</b>	2/18/23

Summary: The CP101 wafer process is discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

**\* All Plating types (PBFREE, TIN/LEAD) for each item listed are included in this notice.**

<b>Central Part Number</b>	<b>Suggested Replacement</b>
BSS52	N/A
CP101-BSS52-CT	N/A
CP101-BSS52-CT20	N/A
CP101-BSS52-WN	N/A

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. If you would like assistance, please visit <https://my.centrasemi.com/submit-inquiry?type=ER> to submit an online inquiry.

**DISCLAIMER:** This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.