

596-00183

Article Number: 596-00183

Thermal Transfer Label, 2.5" X .5", For Use On White Insert 596-00420, PET, White, 500/RL

HellermannTyton



Download spec sheet

## Base Data

**Local Order Number** 596-00183

**Type** NPL63X13

**Color** White (WH)

**Features and Benefits**

- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
- Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
- Labels are UV and chemical resistant for long life in an industrial environment.
- Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

**Short Description** Thermal Transfer Label, 2.5" X .5", For Use On White Insert 596-00420, PET, White, 500/RL

## Product Dimensions

**Length L (Imperial)** 0.5 "

**Length L (Metric)** 12.7 mm

**Self adhesive (Yes/No)** Yes

**Width W (Imperial)** 2.50 "

**Width W (Metric)** 63.5 mm

**Height H (Imperial)** 0.5 "

**Height H (Metric)** 12.7 mm

**Horizontal Repeat HR (imperial)** 2.5 "

**Horizontal Repeat HR (metric)** 63.5 mm

**Print Method** Thermal Transfer

**Vertical Repeat VR (metric)** 15.8 mm

**Vertical Repeat VR (imperial)** 0.625 "

**Width of Liner WL (metric)** 66.67 mm

**Width of Liner WL (imperial)** 2.625 "

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 500

**Package Quantity (Metric)** 500

**Labels per Column** 1

**Labels per Row** 1

## Material and Specifications

---

**Material** Polyester (PET)

**Material Shortcut** PET

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes