

28202.8 PVC-VRT-RH 25X75 YE



Device and installation marker, Length: 75 mm, Width: 25 mm, Colour: Yellow

RAL: 1026

Business data

Article number	28202.8
Article name	PVC-VRT-RH 25X75 YE
GTIN (EAN)	4044211215033
Packaging unit	40
Quantity unit	PC
Number of markers per card	4 ST
Weight per piece (not including packaging)	3.2 g
Weight per piece (including packaging)	3.2 g
Unit of weight	G
Customs number	39204910
Country of origin	IT
Prio-Article	28202.7
Product description	Device and installation marker

28202.8 PVC-VRT-RH 25X75 YE

Technical data

Dimensions

Length	75 mm
Width	25 mm
Diameter of mounting hole	4 mm
Thickness	0.9 mm

Materials

Marker material	PVC
Flammability class UL 94	V-0
Working temperature, min.	-30 °C
Working temperature, max.	60 °C
Processing temperature, min.	10 °C
Processing temperature, max.	40 °C
Silicone-free	✓

Further technical data

Software code	809
Number of bore holes	2 ST

Environmental Product Compliance

REACH Candidate Substance Note	No
--------------------------------	----

Media

28202.8 PVC-VRT-RH 25X75 YE

Accessories

Printer



Thermal transfer printer TTPCard including a power cord, USB cable, dust cover, black thermal transfer film (28010.4), three inlays: CCI-PC-SB 5x5 (28020.0), CCI-PC-CPM-10/BSTR (28027.0), CCI-PC/PVC/PVCF (28041.0), CONTASign PRO software in 16 languages (German, English, French, Italian, Dutch, Spanish, Portuguese, Czech, Polish, Bulgarian, Romanian, Slovenian, Turkish, Chinese, Japanese, Russian) for Windows versions 7, 8, 10. (available for download)

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28000.0</u>	TTPCard Set	4044211207397	1 ST

Inlays

Printer inlay

Article number	Article name	GTIN (EAN)	Packaging unit
<u>28041.0</u>	CCI-PC/PVC/PVCF	4044211208097	1 ST
