MALLORY Mallory So	nalert Products,Inc.	Part #:	SBT5LM0FL
Sales Outline Drawing  Revision:			F
Specifications:	all Pacagnized as canable of me	eting Medical S	noo IEC60601-1-8 AMD2:2020
Sound Level Category:	cUL Recognized as capable of meeting Medical Spec IEC60601-1-8 AMD2:2020  Loud		
Mode of Operation:	Continuous		
Voltage Rating:	3.3 to 5 VDC		
Frequency:	150 to 4000 Hz		
Loudness @ 10cm:	85 to 95 dB(A) Typ.		
Average Current Draw:	<35mA Typ.		
lpk Current*:	300mA		
Housing Material:	ABS 777D Plastic Resin, Black		
Storage Temperature:	-40° to +85° C		
Operating Temperature:	-30° to +65° C		
Weight Typical:	0.6 oz (17g)		
Options: Inches (mi	Please contact factory.  m) cUL Recognized ROHS Compliar		
Before Code Date: 1546	Not cUL Recognized  Ø1.750 [Ø44.5]  2.146 [54.5]	After Code D	Date: 1547 cUL Recognized
	2.538 [64.5]  2.538 [64.5]	FLEX. CONTE 24 AW APPRO BLACK RED W	STRANDED ROL WIRES G INSULATED XX. 6" LONG WIRE (-) VIRE (+)

\*lpk = Instantaneous Peak

tolerances:

±0.01 [±0.3] ±0.005 [±0.1]